

***Rockchip*  
RK817  
*Datasheet***

**Revision 1.01  
Aug.2018**

**Revision History**

Date	Revision	Description
2018-8-28	1.01	Spec change @ power up sequence
2018-3-12	1.0	Initial release

Rockchip Confidential

## Table of Content

Table of Content .....	3
Figure Index .....	5
Table Index	6
Warranty Disclaimer.....	7
Chapter 1 Introduction .....	8
1.2 Feature .....	9
1.3 Typical Application Diagrams .....	10
Chapter 2 Package information .....	11
2.1 Ordering information.....	11
2.2 Top Marking .....	11
2.3 Dimension .....	12
2.4 Pin Assignment.....	13
2.5 Pinout Number Order .....	13
Chapter 3 Electrical Characteristics.....	16
3.1 Absolute Maximum Ratings .....	16
3.2 Recommended Operating Conditions.....	16
3.3 DC Characteristics .....	16
Chapter 4 Function Description .....	21
4.1 POWER UP/POWER DOWN.....	21
4.2 SWITCHING CHARGER.....	21
4.3 POWER PATH MANAGEMENT.....	22
4.4 THERMAL FOLDBACK.....	22
4.5 BATTERY FUEL GAUGE .....	22
4.6 BUCK CONVERTERS .....	22
4.7 BOOST CONVERTER .....	23
4.8 LOW DROPOUT REGULATORS (LDOS) .....	23
4.9 REAL TIME CLOCK (RTC).....	23
4.10 RC OSCILLATOR .....	23
4.11 I2S interface .....	23
4.12 Audio CODEC .....	23
4.13 Head Phone driver .....	23
4.14 ClassD driver .....	24
4.15 POWER SEQUENCE .....	24
Chapter 5 Register Description.....	25
5.1 Register Summary .....	25

---

5.2 Register Description .....	30
Chapter 6 Thermal Management .....	118
6.1 Overview .....	118
6.2 Package Thermal Characteristics .....	118

Rockchip Confidential

## Figure Index

Fig. 1-1RK817 Typical Application Diagram .....	10
Fig. 2-1QFN687mm X 7mm.....	12
Fig. 2-2 Pin Assignment QFN7x7-68(Pitch=0.35mm) .....	13

Rockchip Confidential

## Table Index

Table 4-1 Power up/down sequence(x:BUCK3 voltage determined by external divided resistor) .....	24
Table 6-1 Thermal Resistance Characteristics .....	118

Rockchip Confidential

## Warranty Disclaimer

Rockchip Electronics Co.,Ltd makes no warranty, representation or guarantee (expressed, implied, statutory, or otherwise) by or with respect to anything in this document, and shall not be liable for any implied warranties of non-infringement, merchantability or fitness for a particular purpose or for any indirect, special or consequential damages.

Information furnished is believed to be accurate and reliable. However, Rockchip Electronics Co., Ltd assumes no responsibility for the consequences of use of such information or for any infringement of patents or other rights of third parties that may result from its use.

Rockchip Electronics Co.,Ltd's products are not designed, intended, or authorized for using as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Rockchip Electronics Co.,Ltd's product could create a situation where personal injury or death may occur, should buyer purchase or use Rockchip Electronics Co.,Ltd's products for any such unintended or unauthorized application, buyers shall indemnify and hold Rockchip Electronics Co.,Ltd and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, expenses, and reasonable attorney fees arising out of, either directly or indirectly, any claim of personal injury or death that may be associated with such unintended or unauthorized use, even if such claim alleges that Rockchip Electronics Co.,Ltd was negligent regarding the design or manufacture of the part.

### Copyright and Patent Right

Information in this document is provided solely to enable system and software implementers to use Rockchip Electronics Co., Ltd 's products. There are no expressed or implied copyright licenses granted hereunder to design or fabricate any integrated circuits or integrated circuits based on the information in this document.

**Rockchip Electronics Co.,Ltd does not convey any license under its patent rights nor the rights of others.**

**All copyright and patent rights referenced in this document belong to their respective owners and shall be subject to corresponding copyright and patent licensing requirements.**

### Trademarks

Rockchip and Rockchip™ logo and the name of Rockchip Electronics Co.,Ltd's products are trademarks of Rockchip Electronics Co.,Ltd. and are exclusively owned by Rockchip Electronics Co.,Ltd. References to other companies and their products use trademarks owned by the respective companies and are for reference purpose only.

### Confidentiality

The information contained herein (including any attachments) is confidential. The recipient hereby acknowledges the confidentiality of this document, and except for the specific purpose, this document shall not be disclosed to any third party.

### Reverse engineering or disassembly is prohibited.

**ROCKCHIP ELECTRONICS CO.,LTD. RESERVES THE RIGHT TO MAKE CHANGES IN ITS PRODUCTS OR PRODUCT SPECIFICATIONS WITH THE INTENT TO IMPROVE FUNCTION OR DESIGN AT ANY TIME AND WITHOUT NOTICE AND IS NOT REQUIRED TO UNDATE THIS DOCUMENTATION TO REFLECT SUCH CHANGES.**

### Copyright ©2018 Rockchip Electronics Co.,Ltd.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electric or mechanical, by photocopying, recording, or otherwise, without the prior written consent of Rockchip Electronics Co.,Ltd.

## Chapter 1 Introduction

### 1.1 Overview

The RK817 is a complex power-management integrated circuit (PMIC) integrated CODEC for multi-core system applications powered by a Li-ion or a Li-ion polymer battery cell, or by a 5V input either from an USB port or from an adaptor. The RK817 can provide a complete power management solution with very few external components.

The RK817 provides four configurable synchronous step-down converters. The device also contains 9 LDO regulators, one switch-mode charger, a battery fuel gauge, and the power path management function. Power-up/power-down controller is configurable and can support any customized power-up/power-down sequences (OTP based). A real-time clock (RTC) is also integrated to provide a 32.768-kHz output buffer, and real time function. The RK817 supports 32.768-kHz clock generation based on a crystal oscillator. It also includes Audio CODEC, real ground Head phone driver and ClassD driver.

The switch-mode charger, together with the power path controller integrated in the RK817, allows supplying power to the loads while it is charging the battery. The charger provides functions such as input current limiting, trickle current charging, constant current (CC)/constant voltage (CV) charging, charging termination, charging over time protection, etc. All these functions can be conveniently configured through the I2C digital interface. When an input current limiting is triggered, the power path controller will distribute the input power in a way that the loads have the higher priority than the battery to take the input power. The difference between the input and output power will be used to charge the battery. In a case that the output power required by the loads exceeds the input power, the power path controller will automatically turn on the battery switch so that the battery can supply extra power to the loads together with the input supply. A "battery fuel gauge" is also integrated in the RK817. Using the proprietary algorithms and the sensed battery current and voltage, the gauge can accurately calculate the battery capacity based on the charging/discharging characteristics of the battery preloaded in the system. The gauge then sends the battery capacity information to the processor through the I2C interface. Other functions that the charger provides includes tiny current charging for an over discharged battery, or so called "dead battery", battery temperature monitoring, safe charging timer and over temperature shut down.

The RK817 can dynamically adjust the output voltage of each DC-DC converter, as required by the processor based on the processor's operation status so as to maximize the system efficiency. The output voltages of most channels can be configured through the I2C interface. The inputs of all channels have soft start function, which greatly reduces the inrush current at the startup.

The 2MHz switching frequency allows small size inductors to be used for both buck and boost converters. Also, as all the power switches are integrated on chip, no external power switches and Schottky diodes are needed, which reduces the system cost significantly.

The RK817 is available in a QFN68 7.0 mm x 7.0 mm package, with a 0.35-mm pin pitch.

## 1.2 Feature

- Input range: 3.8V – 5.5V for USB input; 2.7V - 5.5V for BAT input
- Switch mode Li-ion battery charger providing charging current up to 3.5A.
- Power path controller with 4A current path with optional extended external mos.
- Accurate battery fuel gauge with two separate battery voltage and current ADC
- Real time clock (RTC)
- Low standby current of 16uA (at 32.768KHz clock frequency)
- Real ground HeadPhone driver
- 1.3W ClassD PA without external filter inductor
- OTP Programmable power up/down sequences and voltage
- High performance Audio CODEC
  - One internal PLL
  - Support microphone input
  - Support I2S as the digital signal interface for both DAC and ADC
  - Support Automatic Level Control(ALC),limiter and noise gating
  - Support programmable digital and analog gains
  - Audio resolution from 16bits to 32bits
  - Sample rate up to 192KHz
  - Provides master and slave work mode, software configurable
  - Support 3 I2S formats (normal, left-justified, right-justified)
  - Support PDM mode(external input PCLK)
- Power channels:
  - ◆ CH1:Synchronous BUCK converter,2.5A max
  - ◆ CH2:Synchronous BUCK converter,2.5A max
  - ◆ CH3:Synchronous BUCK converter,1.5A max
  - ◆ CH4:Synchronous BUCK converter,1.5A max
  - ◆ CH5:Synchronous BOOST converter,1.5A max(Can not be used at the same time with the charger function)
  - ◆ CH6~CH7,CH9~CH14:LDOs, 400mA max
  - ◆ CH8:Low noise, high PSRR LDO,100mA max
  - ◆ CH15:OTG Switch,1.5A max(Can not be used at the same time with the charger function)
- Package:7mmx7mm QFN68

## 1.3 Typical Application Diagrams





Fig. 1-1RK817 Typical Application Diagram

## Chapter 2 Package information

### 2.1 Ordering information

Orderable Device	RoHS status	Package	Package Qty
RK817-1	RoHS	QFN68(7X7)	2600ea/inner box* 6 inner boxes/outer box

### 2.2 Top Marking



## 2.3 Dimension




Fig. 2-1QFN687mm X 7mm

DESCRIPTION	SYMBOL	MILLIMETER		
		MIN	NOM	MAX
TOTAL THICKNESS	A	0.70	0.75	0.80
STAND OFF	A1	0	0.035	0.05
MOLD THICKNESS	A2	-	0.55	0.57
MATERIAL THICKNESS	A3	-	0.203 <sub>REF</sub>	-
PACKAGE SIZE	D	-	7 <sub>BSC</sub>	-
	E	-	7 <sub>BSC</sub>	-
EP SIZE	D1	5.39	5.49	5.59
	E1	5.39	5.49	5.59
LEAD LENGTH	L	0.30	0.4	0.50
LEAD PITCH	e	0.35 <sub>BSC</sub>		
LEAD WIDTH	b	0.1	0.15	0.2
LEAD POSITION OFFSET	aaa	0.07		
LEAD COPLANARITY	bbb	0.08		
PACKAGE EDGE PROFILE	ccc	0.10		
MOLD FLATNESS	ddd	0.10		
EP POSITION OFFSET	eee	0.10		
	fff	0.05		

## Note:

1. Coplanarity applies to leads, corner leads and die attach pad.
2. Dimension b applies to metalized terminal and is measured between 0.15mm and 0.30mm from the terminal tip. If the terminal has the optional radius on the other end of the terminal, the dimension b should not be measure in that radius area.

## 2.4 Pin Assignment




Fig. 2-2 Pin Assignment QFN7x7-68(Pitch=0.35mm)

## 2.5 Pinout Number Order

PIN NO	PIN NAME	PIN DESCRIPTION
1	SCL	I2C clock input
2	SDA	I2C data input and output(Open drain output)
3	LDO7	LDO7 output
4	VCC7	Power supply of LDO7/8/9
5	LDO8	LDO8 output
6	LDO9	LDO9 output
7	INT	Interrupt request pin, open drain
8	FB2	Output feedback voltage of buck2
9	SW2	Switching node of buck2
10	VCC2	Power supply of buck2
11	VCC1	Power supply of buck1
12	SW1	Switching node of buck1
13	FB1	Output feedback voltage of buck1
14	LRCLK	The I2S framing clock
15	BCLK	The I2S bit clock
16	MCLK	The I2S main clock input pin
17	SDI	The I2S DAC input data
18	SDO/PDMDATA	The I2S ADC output data/PDM Data for the DSADC
19	PDMCLK	PDM CLK for the DSADC OUTPUT
20	LDO3	LDO3 output

PIN NO	PIN NAME	PIN DESCRIPTION
21	LDO2	LDO2 output
22	VCC5	Power supply of LDO1/2/3
23	LDO1	LDO1 output
24	VCC3	Power supply of buck3
25	SW3	Switching node of buck3
26	VBUCK3	Output voltage of buck3
27	FB3	Output feedback voltage of buck3
28	LDO4	LDO4 output, internal power supply for I2S interface(Pin14~Pin19)
29	LDO5	LDO5 output
30	VCC6	Power supply of LDO4/5/6
31	LDO6	LDO6 output
32	SPKP_OUT	Positive speaker driver output
33	VCC_SPK_HP	Power supply for speaker and head phone
34	SPKN_OUT	Negative speaker driver output.
35	VCC_CPVSS	Negative power supply for the headphone
36	CPN	Negative switching node of the charger pump
37	CPP	Positive switching node of the charger pump.
38	VCC_CPVDD	Positive power supply for the headphone
39	HPL_OUT	Left channel output of the headphone
40	HP_SNS	Reference ground for the headphone
41	HPR_OUT	Right channel output of the headphone
42	MICIN	Negative input of the Microphone
43	MICIP	Positive input of the Microphone
44	VCC_1P8A	Power supply for internal 1.8V analog circuit
45	VCC_RTC	Power supply filter
46	VREF	Internal reference voltage
47	GNDREF	Reference ground
48	VCC_1P8D	Power supply for internal 1.8V digital circuit
49	SLEEP	Sleep mode control input
50	XIN	32.768KHz crystal oscillator input
51	XOUT	32.768KHz crystal oscillator output
52	PWRON	Power on key input, active low, internal 17k resistor pull high to VCC_RTC
53	SW5	Switching node of charger/boost
54	MIDU/BOOST	Middle point of USB power supply / boost output
55	USB/OTG	USB power supply/OTG output
56,57	BAT	Positive battery terminal
58,59	SYS	DC-DC regulator output to power the system load and charge the battery
60	GATE/GPIO	Control the external PMOS to reduce the conduction resistance or GPIO function by register setting
61	TS/GPIO	Connect the thermistor from this pin to ground. Or it can be used as an analog input pin of internal ADC if the control bit is set to ADC function or GPIO function by register setting
62	SNSP	Bat charging and discharging sense current positive pin
63	SNSN	Bat charging and discharging sense current negative pin
64	FB4	Output feedback voltage of buck4
65	SW4	Switching node of buck4
66	VCC4	Power supply of buck4

PIN NO	PIN NAME	PIN DESCRIPTION
67	RESETB	Reset pin after power on, active low;
68	CLK32K	32.768KHz clock output, open drain
Exposed pad	Exposed ground	Ground

Rockchip Confidential

## Chapter 3 Electrical Characteristics

### 3.1 Absolute Maximum Ratings

Parameter	Min	Max	Units
Voltage range on pins USB/OTG, MIDU/BOOST, SWx, VCC1~7,VCC_RTC,VCC_SPK_HP,LDOx, SYS, BAT, FBx,VBUCK3,SPKP_OUT,SPKN_OUT	-0.3	6.5	V
Voltage range on pin CLK32K,RESETB, SLEEP,SCL,SDA,INT,PWRON,XIN,SOUT, TS/GPIO,GATE/GPIO,	-0.3	6.5	V
Voltage range on pins LRCLK,BCLK,MCLK,SDI,SDO/PDMCLK,PDMCLK,	-0.3	6.5	V
Voltage range on pins SNSP,SNSN,VREF,VCC_1P8D,VCC_1P8A,MIC1N,MIC1P	-0.2	1.98	V
Voltage range on pins HP_SNS,HPR_OUT,HPL_OUT	-2.7	2.7	V
Voltage range on pins VCC_CPVDD,CPP	-0.3	2.7	V
Voltage range on pins VCC_CPVSS,CPP	-2.7	0.3	V
Storage temperature range, $T_s$	-40	150	°C
Operating temperature range, $T_j$	-40	125	°C
Maximum Soldering Temperature, $T_{SOLDER}$		300	°C

Note:

Exposure to the conditions exceeded absolute maximum ratings may cause the permanent damages and affect the reliability and safety of both device and systems using the device. The functional operations cannot be guaranteed beyond specified values in the recommended conditions.

### 3.2 Recommended Operating Conditions

Parameter	Min	TYP	Max	Units
Voltage range on pins USB/OTG	4	5	5.5	V
Power Dissipation			2	W

### 3.3 DC Characteristics

Test conditions: USB=5.0V,TA=25°C for typical values, unless otherwise noted.

PARAMETERS	SYMBOL	CONDITION	MIN	TYP	MAX	UNIT
<b>USB INPUT</b>						
USB Operating Range	$V_{USB}$		3.8	5	5.5	V
USB Input Current Limit	$I_{USB}$	Default	400	450	500	mA
		Max current	2.8	3	3.2	A
USB input VoltageLimit		0.1V step, default=4.4V	4		4.7	V
<b>CHARGER</b>						
Charge current	$I_{CC}$	default=2A	0.5		3.5	A
<b>A/D CONVERTER</b>						
Voltage measuring ADC resolution				12		bits

PARAMETERS	SYMBOL	CONDITION	MIN	TYP	MAX	UNIT
Range of USB/OTG voltage measurement			1		6	V
Range of BAT voltage measurement			0		4.6	V
Range of SYS voltage measurement			1		6	V
Range of TS voltage measurement			0		1.2	V
Current measuring ADC resolution				15		bits
Range of Current ADC measurement			-56.25		56.25	mV
<b>SYS INPUT</b>						
BAT to SYS Resistance		I <sub>SYS</sub> =200mA , V <sub>BAT</sub> =4.2V		0.08	0.12	Ω
BAT to SYS Current Limit	I <sub>BATLIM</sub>	0.5A step,default=3.5A	2		4	A
		SYS short		200		mA
<b>CH1: BUCK DC-DC CONVERTER(BUCK1)</b>						
Input supply voltage range	V <sub>INPUT1</sub>		2.7		5.5	V
Voltage Adjustable Range, 7bit	V <sub>FB1</sub>	Step=12.5mV(0.5 V< V <sub>FB1</sub> <1.5) Step=100mV(1.5 V< V <sub>FB1</sub> <2.4)	0.5		2.4	V
Rated output current	I <sub>MAX1</sub>			2.5		A
Conversion Efficiency(Vin=3.8V,Vout=1V) Iout=2.5A Iout=0.3A				70 85		%
<b>CH2: BUCK DC-DC CONVERTER(BUCK2)</b>						
Input supply voltage range	V <sub>INPUT2</sub>		2.7		5.5	V
Voltage Adjustable Range, 7bit	V <sub>FB2</sub>	Step=12.5mV(0.5 V< V <sub>FB2</sub> <1.5) Step=100mV(1.5 V< V <sub>FB2</sub> <2.4)	0.5		2.4	V
Rated output current	I <sub>MAX2</sub>			2.5		A
Conversion Efficiency(Vin=3.8V,Vout=1V) Iout=2.5A Iout=0.3A				70 85		%
<b>CH3: BUCK DC-DC CONVERTER(BUCK3)</b>						
Input supply voltage range	V <sub>INPUT3</sub>		2.7		5.5	V
Feedback Voltage, Default	V <sub>FB3(Default)</sub>	Selection of external resistor divider	0.784	0.8	0.816	V
Voltage Adjustable Range, 7bit	V <sub>FB3</sub>	Step=12.5mV(0.5 V< V <sub>FB3</sub> <1.5) Step=100mV(1.5 V< V <sub>FB3</sub> <2.4) Selection of internal resistor divider	0.5		2.4	V
Rated output current	I <sub>MAX3</sub>			1.5		A
Conversion Efficiency(Vin=3.8V,Vout=1.5V) ) Iout=1.5A Iout=0.3A				80 88		%

PARAMETERS	SYMBOL	CONDITION	MIN	TYP	MAX	UNIT
<b>CH4: BUCK DC-DC CONVERTER(BUCK4)</b>						
Input supply voltage range	$V_{INPUT4}$		2.7		5.5	V
Voltage Adjustable Range, 7bit	$V_{FB4}$	Step=12.5mV(0.5 $V < V_{FB4} < 1.5$ ) Step=100mV(1.5 $V < V_{FB4} < 3.4$ )	0.5		3.4	V
Rated output current	$I_{MAX4}$			1.5		A
Conversion Efficiency, ( $V_{IN}=3.8V, V_{OUT}=3.3V$ ) $I_{out}=1.5A$ $I_{out}=300mA$				85 95		%
<b>CH5: BOOST DC-DC CONVERTER (BOOST)</b>						
Input supply voltage range	$V_{INPUT5}$		2.7		4.4	V
Output Voltage	$V_{FB5}$	Step=0.1v,default =5v	4.7		5.4	V
Voltage, Default	$V_{FB5}(\text{Default})$		4.90	5.0	5.10	V
Rated output current	$I_{MAX5}$			1.5		A
<b>CH6: LDO1</b>						
Input supply voltage range	$V_{INPUT6}$		2		5.5	V
$V_{OUT}$	$V_{OUT6}$	Step=25mV	0.6		3.4	V
Rated output current	$I_{MAX6}$	$V_{INPUT6}=3.6V,$ $V_{OUT6}=3.3V$ RegLDO1_MAX=1		400		mA
		$V_{INPUT6}=2V,$ $V_{OUT6}=1.8V$		200		mA
<b>CH7: LDO2</b>						
Input supply voltage range	$V_{INPUT7}$		2		5.5	V
$V_{OUT}$	$V_{OUT7}$	Step=25mV	0.6		3.4	V
Rated output current	$I_{MAX7}$	$V_{INPUT7}=3.6V,$ $V_{OUT7}=3.3V$ RegLDO2_MAX=1		400		mA
		$V_{INPUT7}=2V,$ $V_{OUT7}=1.8V$		200		mA
<b>CH8: LDO3</b>						
Input supply voltage range	$V_{INPUT8}$		2		5.5	V
$V_{OUT}$	$V_{OUT8}$	Step=25mV	0.6		3.4	V
Power Supply Reject Ratio ( $f = 10kHz$ , $V_{OUT9}=1.1V$ )	PSRR8			65		dB
Rated output current	$I_{MAX8}$	$V_{INPUT8}=3.6V,$ $V_{OUT8}=3.3V$ RegLDO3_MAX=1		100		mA
		$V_{INPUT8}=2V,$ $V_{OUT8}=1.8V$		100		mA
<b>CH9: LDO4</b>						
Input supply voltage range	$V_{INPUT9}$		2		5.5	V
$V_{OUT}$	$V_{OUT9}$	Step=25mV	0.6		3.4	V
Rated output current	$I_{MAX9}$	$V_{INPUT9}=3.6V,$ $V_{OUT9}=3.3V$ RegLDO4_MAX=1		400		mA
		$V_{INPUT9}=2V,$ $V_{OUT9}=1.8V$		200		mA
<b>CH10: LDO5</b>						
Input supply voltage range	$V_{INPUT10}$		2		5.5	V
$V_{OUT}$	$V_{OUT10}$	Step=25mV	0.6		3.4	V
Rated output current	$I_{MAX10}$	$V_{INPUT10}=3.6V, V_{OUT10}=3.3V$ RegLDO5_MAX=1		400		mA
		$V_{INPUT10}=2V,$ $V_{OUT10}=1.8V$		200		mA
<b>CH11: LDO6</b>						
Input supply voltage range	$V_{INPUT11}$		2		5.5	V

PARAMETERS	SYMBOL	CONDITION	MIN	TYP	MAX	UNIT
$V_{OUT}$	$V_{OUT11}$	Step=25mV	0.6		3.4	V
Rated output current	$I_{MAX11}$	$V_{INPUT11}=3.6V$ , $V_{OUT11}=3.3V$ RegLDO6_MAX=1		400		mA
		$V_{INPUT11}=2V$ , $V_{OUT11}=1.8V$		200		mA
<b>CH12: LDO7</b>						
Input supply voltage range	$V_{INPUT12}$		2		5.5	V
$V_{OUT}$	$V_{OUT12}$	Step=25mV	0.6		3.4	V
Rated output current	$I_{MAX12}$	$V_{INPUT12}=3.6V$ , $V_{OUT12}=3.3V$ RegLDO7_MAX=1		400		mA
		$V_{INPUT12}=2V$ , $V_{OUT12}=1.8V$		200		mA
<b>CH13: LDO8</b>						
Input supply voltage range	$V_{INPUT13}$		2		5.5	V
$V_{OUT}$	$V_{OUT13}$	Step=25mV	0.6		3.4	V
Rated output current	$I_{MAX13}$	$V_{INPUT13}=3.6V$ , $V_{OUT13}=3.3V$ RegLDO8_MAX=1		400		mA
		$V_{INPUT13}=2V$ , $V_{OUT13}=1.8V$		200		mA
<b>CH14: LDO9</b>						
Input supply voltage range	$V_{INPUT14}$		2		5.5	V
$V_{OUT}$	$V_{OUT14}$	Step=25mV	0.6		3.4	V
Rated output current	$I_{MAX14}$	$V_{INPUT14}=3.6V$ , $V_{OUT14}=3.3V$ RegLDO9_MAX=1		400		mA
		$V_{INPUT14}=2V$ , $V_{OUT14}=1.8V$		200		mA
<b>CH15: OTG</b>						
Input supply voltage range	$V_{INPUT15}$		4.7		5.4	V
$R_{DSON\_OTG}$				90		mohm
Rated output current	$I_{MAX15}$			1500		mA
<b>ClassD Audio PA</b>						
Input supply voltage range	$V_{INPUT14}$	$V_{CC\_SPK\_HP}$	2.7		5.5	V
THD+N		1KHz, $P_o=0.4W_{rms}$ , $V_{CC\_SPK\_HP}=3.8V$		0.1		%
RMS Power		8 ohm load, $V_{CC\_SPK\_HP}=3.8V$ , THD+N=1%		700		mW
		8 ohm load, $V_{CC\_SPK\_HP}=5V$ , THD+N=1%		1100		mW
		8 ohm load, $V_{CC\_SPK\_HP}=5V$ , THD+N=10%		1300		mW
PSRR		217Hz, $V_{CC\_SPK\_HP}=200mV_{pk-pk}+3.8V$		65		dB
Output Offset Voltage		$V_{CC\_SPK\_HP}=3.8V$		+/- 15		mV
Noise Level		$V_{CC\_SPK\_HP}=3.8V$ 0dB Gain, 80hm, A-weighted		100		uV
Efficiency		$V_{CC\_SPK\_HP}=3.8V, 0.4W, 80hm$ with 68uH, 1Khz		88		%

PARAMETERS	SYMBOL	CONDITION	MIN	TYP	MAX	UNIT
Quiescent current		No load, VCC_SPK_HP =3.8		4		mA
<b>DAC to Head phone outputs</b>						
Full scale output level		RL=32ohm		0.5		Vrms
		RL=300ohm		0.8		Vrms
Signal to Noise Ratio	SNR	A-weighted RL=32ohm, - 60dBFS, Fs=48KHz		97		dB
Total Harmonic Distortion + Noise	THD+N	A-weighted RL=32ohm - 3dBFS Fs=48KHz		-75		dB
<b>ADC stereo input</b>						
Full scale input voltage		Vpp		1		V
SNR		A-weighted, - 60dBFS,Fs=48KH z		88		dB
THD+N		A-weighted 997Hz -3dBFS Differential input signal, Fs=48KHz		-75		dB
<b>I2C interface</b> (7bits I2C address is 0x20)						
SCL clock frequency	f <sub>SCL</sub>			1000		KHz
<b>LOGIC INPUT</b>						
Input LOW-Level Voltage	V <sub>IL</sub>			0.4		V
Input HIGH-Level Voltage: LRCLK,BCLK,MCLK,SDI,PDMCLK	V <sub>IH1</sub>		LDO4* 0.7		VCC_RT C	V
Input HIGH-Level Voltage: SCL,SDA,SLEEP,PWRON,TS/GPI O,GATE/GPIO,RESETB	V <sub>IH2</sub>		VCC_1P 8D*0.7		VCC_RT C	V
<b>LOGIC OUTPUT</b>						
LOW-Level Output Voltage, 3.0 mA sink current	V <sub>OL</sub>			0.4		V
HIGH-Level Output Voltage, 3.0 mA source current: LRCLK,BCLK,SDO/PDMDATA	V <sub>OH1</sub>		LDO4- 0.4		LDO4	V
HIGH-Level Output Voltage, 3.0 mA source current: TS/GPIO,GATE/GPIO	V <sub>OH2</sub>		VCC_RT C-0.4		VCC_RT V	V
<b>OPEN DRAIN OUTPUT PIN</b>						
CLK32K,RESETB,INT,SDA						

## Chapter 4 Function Description

### 4.1 POWER UP/POWER DOWN

The RK817 can be powered by either a battery, or an external power supply through the USB port. When the PMIC is powered by a battery only, pressing the PWRON key powers up the PMIC. All the power channels start up at the default output voltages with a preset power up sequence, which has 2mS intervals between the channels. When the power up process is done, the RESETB turns to high logic level to inform the processor that all the power rails are up and stable. And now the processor can communicate with the PMIC to re-configure the output voltage of each power channel if needed.

To power down the PMIC, the processor needs to issue a “power down” signal through the I<sup>2</sup>C interface. Upon receiving the power down signal, the PMIC first saves all the information on the existing states, and then switches the RESETB to low logic level. At this point, the power channels start to be turned off one after another with the power down sequence. If for any reason the processor fails to issue the power down signal, the PMIC can be powered off by “pressing and holding” the PWRON key.

In a case where a battery is the sole power supply and the PMIC is in off state, when an external power supply is plugged into the USB, the PMIC will first check to see if this is a valid power supply. If the power supply from the USB is valid, then the power channels are turned on and the battery is charged.

### 4.2 SWITCHING CHARGER

The RK817 has integrated a switch mode charger, which provides the functions like trickle current charging, constant current charging, constant voltage charging, charging termination, automatic recharging, battery temperature monitoring, charging timer and thermal feedback protection. The values of constant current and constant voltage charging can be set through I<sup>2</sup>C interface.

The input average current limit function allows as large as possible a charging current to be used without having to worry about the input current exceeding the maximum current allowed by the USB port. The input current limits can be configured through I<sup>2</sup>C interface. For example, when an USB port is used as the input, the input current limit can be configured to either 450mA, or 850mA, to meet the requirements of USB2.0 and USB3.0 respectively.

The charger also has a timer function which sets the maximum charging time for trickle, constant current and constant voltage charging, respectively. If the charging does not complete when a preset maximum charging time is reached, the charging is terminated.

The battery temperature can be monitored through the TS pin. A battery typically has a thermistor inside. The RK817 sinks a constant current into the thermistor and senses the voltage across the thermistor through an internal ADC. A safe charging temperature range is preset in the PMIC. The charging can proceed normally if the battery temperature falls within the preset range. If, however, the battery temperature goes either above the upper limit or below the lower limit of the preset range, the charging will pause until the battery temperature goes back in the preset range. If the value of the available thermistor is either too large or too small, a normal resistor can be connected in series or in parallel with the thermistor so that the sensed voltage fits the ADC’s input range.

During Charging, Vsys will be set to 3.6V when the battery voltage is below 3.6V. This design is to guarantee that when an external power supply is plugged into the USB port to charge the battery while the battery voltage is low, the Vsys is already at 3.6V, which allows the PMIC to start up quickly without having to wait for the Vsys ramping up.

## 4.3 POWER PATH MANAGEMENT

A power path management function is integrated in the RK817, which, together with the accurate input current limit function, can provide intelligent power path control. In a power path control process, the PMIC gives the outputs, or the system loads, the highest priority of using the input power. The battery is getting charged only if the input power is greater than the output power required by the system loads. The intelligent power path control function automatically reduces the charging current when the output power required by the loads increases. In an extreme case where the required output power is greater than the input power, the charging current will be cut off and the battery will join the input power supply to provide power to the load. This is how the intelligent power path control works: As the system power loading increases, the PMIC will draw more input current from the power supply to meet the output power requirement while keep the charging current unchanged. If the system power loading continues to increase to the point where the input current limit is reached, then the PMIC will lower the charging current so that enough power still goes to the load. If the system power loading further increases and due to the input current limit, the input power can not meet the output power requirement, then the battery will start to discharge to supply power to the load together with the USB power supply. If for some reason the USB is unplugged, the battery will automatically switched in to take over the USB power supply and provide full power to the load. The wide power path loop bandwidth allows all the above mentioned power path switching transient to be quick and seamless and therefore no overshoot and notch occur at the system and output voltages.

To minimize the loss from the voltage drop along the current path when the battery is charged or discharged, a  $100m\Omega$  MOSFET is integrated in the RK817 to serve as a control switch as well as the power switch of the switching mode battery charger.

## 4.4 THERMAL FOLDBACK

Generally speaking, the higher the operating junction temperature is, the shorter the chip's life time. Therefore, keeping the operating junction temperature as low as possible is one of the keys in reliability design. The RK817 provides a thermal feedback protection function for charging process. When the die temperature reaches a preset value, the PMIC will lower the charging current so as to keep the die temperature within an appropriate range. The life time of the PMIC equipped with this function can be reliably prolonged and no overheat damage will occur.

## 4.5 BATTERY FUEL GAUGE

The RK817 provides an accurate battery fuel gauge. A 12-bit battery voltage ADC and a 15-bit battery current ADC are integrated in the RK817 to collect the information on the battery, such as battery voltage, charging/discharging status, battery temperature, etc. Using the proprietary algorithms and the information collected by the ADC, the battery fuel gauge can accurately calculate the battery capacity based on the charging/discharging characteristics of the battery preloaded in the system. The gauge then sends the battery capacity information to the processor through the I<sup>2</sup>C interface.

## 4.6 BUCK CONVERTERS

The RK817 provides four high current synchronous buck converters, which deliver up to 2.5A, 2.5A, 1.5A and 1.5A, respectively. An enhanced COT architecture is used, which improves the transient response significantly. All output voltages can be adjusted dynamically during operation through DVS (Dynamic Voltage Scaling), which guarantees a linear and gradual voltage ramping up and down. A complete set of protection functions, such as short circuit protection, is implemented in the buck converters too.

The key parameters such as operating mode, output voltage, DVS change rate, and output current limit can be configured through the I<sup>2</sup>C interface.

## 4.7 BOOST CONVERTER

The synchronous boost converter has 1.5A current capability and is used to power the OTG. The OTG has a built-in current limiting switch, which can effectively protect the boost converter from being damaged if a short circuit occurs at the OTG port.

As the USB input port and the OTG output port share a same pin, when the USB port is being used as a power supply and charging the battery, the OTG switch is forbidden to be turned on. Only when there is no external power supply plugged into the USB port, can the OTG be turned on and serve as a power supply.

The key parameters such as operating mode, output voltage, and output current limit can be configured through the I<sup>2</sup>C interface.

## 4.8 LOW DROPOUT REGULATORS (LDOS)

The RK817 also integrates nine LDOs, with 8 LDOs (Ch6, Ch7, Ch9 ~Ch14) capable of providing up to 400mA and one LDO (CH8 ) providing maximum 100mA. The LDO on CH8 is a low noise, high PSRR LDO . The parameters such as output voltage in the different operating modes can be adjusted through the I<sup>2</sup>C interface.

## 4.9 REAL TIME CLOCK (RTC)

The RK817 integrates a crystal oscillator buffer and a real time clock (RTC). The buffer works with an external 32.768kHz crystal oscillator. With the RTC function, the PMIC provides second/minute/hour/day/month/year information, alarm wake up as well as time calibration. The RK817 provides one channel of 32.768kHz clocks with open drain outputs, where it is default on and is controlled through I<sup>2</sup>C interface.

## 4.10RC OSCILLATOR

The RK817 integrates an RC oscillator. If the external crystal oscillator is not connected, the chip will be driven by the internal RC oscillator. Without external crystal oscillator , the system costs can be saved, but the RTC and the fuel gauge will be inaccurate.

## 4.11I2S interface

The RK817 supports I2S for the digital audio data interface. The I2S/PCM audio digital interface is used to input data to a stereo DAC or output data from a stereo ADC. The I2S/PCM audio interface can be configured to Master mode or Slave mode. In Master Mode, BCLK and LRCLK are configured as output, but MCLK is fixed as input. In Slave Mode, BCLK and LRCLK are configured as input, and the MCLK is still as input.

## 4.12Audio CODEC

The RK817 integrates a high performance stereo ADC and a high performance stereo DAC.

The audio recording path is composed of MIC\_PGA and audio ADC.

## 4.13Head Phone driver

The RK817 integrates a stereo output and with cap-free type headphone amplifier. It doesn't need to connect external capacitance, and can connect to earphone device directly.

## 4.14 ClassD driver

The RK817 integrates a high efficiency stereo Class-D type amplifier capable of delivering 1.3W of power on an 8ohm BTL load from a 5V power supply. It integrates over-current protection.

## 4.15 POWER SEQUENCE

		RK817-1		
	Range of output voltage	Maximum output current	Default voltage	Start up sequence
BUCK1	0.5V-2.4V	2.5A	1.1V	1
BUCK2	0.5V-2.4V	2.5A	1.1V	1
BUCK3	X(external divided resistor) Or 0.5V-2.4v(internal divided resistor)	1.5A	x	3
BUCK4	0.5V-3.4V	1.5A	3.0V	4
BOOST	4.7V-5.4V	1.5A	5.0V	OFF
LDO1	0.6V-3.4V	400mA	1.0V	2
LDO2	0.6V-3.4V	400mA	1.8V	2
LDO3	0.6V-3.4V	400mA	1.0V	1
LDO4	0.6V-3.4V	100mA	3.0V	4
LDO5	0.6V-3.4V	400mA	3.0V	4
LDO6	0.6V-3.4V	400mA	3.0V	4
LDO7	0.6V-3.4V	400mA	2.8V	OFF
LDO8	0.6V-3.4V	400mA	1.8V	OFF
LDO9	0.6V-3.4V	400mA	1.5V	OFF
OTG	Equals to BOOST	1.5A	5.0V	OFF

Table 4-1 Power up/down sequence(x:BUCK3 voltage determined by external divided resistor)

## Chapter 5 Register Description

### 5.1 Register Summary

Name	Offset	Size	Reset Value	Description
RTC_SECONDS	0x0000	B	0x00	
RTC_MINUTES	0x0001	B	0x00	
RTC_HOURS	0x0002	B	0x09	
RTC_DAYS	0x0003	B	0x04	
RTC_MONTHS	0x0004	B	0x08	
RTC_YEARS	0x0005	B	0x17	
RTC_WEEKS	0x0006	B	0x05	
RTC_ALARM_SECONDS	0x0007	B	0x00	
RTC_ALARM_MINUTES	0x0008	B	0x00	
RTC_ALARM_HOURS	0x0009	B	0x00	
RTC_ALARM_DAYS	0x000a	B	0x01	
RTC_ALARM_MONTHS	0x000b	B	0x01	
RTC_ALARM_YEARS	0x000c	B	0x00	
RTC_RTC_CTRL	0x000d	B	0x00	
RTC_RTC_STATUS	0x000e	B	0x82	
RTC_RTC_INT	0x000f	B	0x00	
RTC_RTC_COMP_LSB	0x0010	B	0x00	
RTC_RTC_COMP_MSB	0x0011	B	0x00	
CODEC_DTOP_VUCTL	0x0012	B	0x03	
CODEC_DTOP_VUCTIME	0x0013	B	0x00	
CODEC_DTOP_LPT_SRST	0x0014	B	0x00	
CODEC_DTOP_DIGEN_CLKE	0x0015	B	0x00	
CODEC_AREF_RTCFG1	0x0017	B	0x06	
CODEC_AADC_CFG0	0x0018	B	0xc8	
CODEC_DADC_VOLL	0x001a	B	0x00	
CODEC_DADC_VOLR	0x001b	B	0x00	
CODEC_DADC_SR_ACL0	0x001e	B	0x00	
CODEC_DADC_ALC1	0x001f	B	0x00	
CODEC_DADC_ALC2	0x0020	B	0x00	
CODEC_DADC_NG	0x0021	B	0x00	
CODEC_DADC_HPF	0x0022	B	0x00	
CODEC_DADC_RVOLL	0x0023	B	0xff	
CODEC_DADC_RVOLR	0x0024	B	0xff	
CODEC_AMIC_CFG0	0x0027	B	0x70	
CODEC_AMIC_CFG1	0x0028	B	0x00	
CODEC_DMIC_PGA_GAIN	0x0029	B	0x66	
CODEC_DMIC_LMT1	0x002a	B	0x00	
CODEC_DMIC_LMT2	0x002b	B	0x00	
CODEC_DMIC_NG1	0x002c	B	0x00	

Name	Offset	Size	Reset Value	Description
CODEC_DMIC_NG2	0x002d	B	0x00	
CODEC_ADAC_CFG1	0x002f	B	0x07	
CODEC_DDAC_POPD_DACST	0x0030	B	0x82	
CODEC_DDAC_VOLL	0x0031	B	0x00	
CODEC_DDAC_VOLR	0x0032	B	0x00	
CODEC_DDAC_SR_LMT0	0x0035	B	0x00	
CODEC_DDAC_LMT1	0x0036	B	0x00	
CODEC_DDAC_LMT2	0x0037	B	0x00	
CODEC_DDAC_MUTE_MIXCTL	0x0038	B	0xa0	
CODEC_DDAC_RVOLL	0x0039	B	0xff	
CODEC_DDAC_RVOLR	0x003a	B	0xff	
CODEC_AHP_ANTI0	0x003b	B	0x00	
CODEC_AHP_ANTI1	0x003c	B	0x00	
CODEC_AHP_CFG0	0x003d	B	0xe0	
CODEC_AHP_CFG1	0x003e	B	0x1f	
CODEC_AHP_CP	0x003f	B	0x09	
CODEC_ACLASSD_CFG1	0x0040	B	0x69	
CODEC_ACLASSD_CFG2	0x0041	B	0x44	
CODEC_APPL_CFG0	0x0042	B	0x04	
CODEC_APPL_CFG1	0x0043	B	0x00	
CODEC_APPL_CFG2	0x0044	B	0x30	
CODEC_APPL_CFG3	0x0045	B	0x19	
CODEC_APPL_CFG4	0x0046	B	0x65	
CODEC_APPL_CFG5	0x0047	B	0x01	
CODEC_DI2S_CKM	0x0048	B	0x01	
CODEC_DI2S_RSD	0x0049	B	0x00	
CODEC_DI2S_RXCR1	0x004a	B	0x00	
CODEC_DI2S_RXCR2	0x004b	B	0x17	
CODEC_DI2S_RXCMD_TSD	0x004c	B	0x00	
CODEC_DI2S_TXCR1	0x004d	B	0x00	
CODEC_DI2S_TXCR2	0x004e	B	0x17	
CODEC_DI2S_TXCR3_TXCMD	0x004f	B	0x00	
gas_gauge_ADC_CONFIG0	0x0050	B	0x8c	
gas_gauge_ADC_CONFIG1	0x0055	B	0x30	
gas_gauge_GG_CON	0x0056	B	0x44	
gas_gauge_GG_STS	0x0057	B	0x00	
gas_gauge_RELAX_THRE_H	0x0058	B	0x00	
gas_gauge_RELAX_THRE_L	0x0059	B	0x60	
gas_gauge_RELAX_VOL1_H	0x005a	B	0x00	
gas_gauge_RELAX_VOL1_L	0x005b	B	0x00	
gas_gauge_RELAX_VOL2_H	0x005c	B	0x00	
gas_gauge_RELAX_VOL2_L	0x005d	B	0x00	
gas_gauge_RELAX_CUR1_H	0x005e	B	0x00	

Name	Offset	Size	Reset Value	Description
gas_gauge_RELAX_CUR1_L	0x005f	B	0x00	
gas_gauge_RELAX_CUR2_H	0x0060	B	0x00	
gas_gauge_RELAX_CUR2_L	0x0061	B	0x00	
gas_gauge_OCV_THRE_VOL	0x0062	B	0x00	
gas_gauge_OCV_VOL_H	0x0063	B	0x00	
gas_gauge_OCV_VOL_L	0x0064	B	0x00	
gas_gauge_OCV_VOL0_H	0x0065	B	0x00	
gas_gauge_OCV_VOL0_L	0x0066	B	0x00	
gas_gauge_OCV_CUR_H	0x0067	B	0x00	
gas_gauge_OCV_CUR_L	0x0068	B	0x00	
gas_gauge_OCV_CUR0_H	0x0069	B	0x00	
gas_gauge_OCV_CUR0_L	0x006a	B	0x00	
gas_gauge_PWRON_VOL_H	0x006b	B	0x00	
gas_gauge_PWRON_VOL_L	0x006c	B	0x00	
gas_gauge_PWRON_CUR_H	0x006d	B	0x00	
gas_gauge_PWRON_CUR_L	0x006e	B	0x00	
gas_gauge_OFF_CNT	0x006f	B	0x00	
gas_gauge_Q_INIT_H3	0x0070	B	0x00	
gas_gauge_Q_INIT_H2	0x0071	B	0x00	
gas_gauge_Q_INIT_L1	0x0072	B	0x00	
gas_gauge_Q_INIT_L0	0x0073	B	0x00	
gas_gauge_Q_PRES_H3	0x0074	B	0x00	
gas_gauge_Q_PRES_H2	0x0075	B	0x00	
gas_gauge_Q_PRES_L1	0x0076	B	0x00	
gas_gauge_Q_PRES_L0	0x0077	B	0x00	
gas_gauge_BAT_VOL_H	0x0078	B	0x00	
gas_gauge_BAT_VOL_L	0x0079	B	0x00	
gas_gauge_BAT_CUR_H	0x007a	B	0x00	
gas_gauge_BAT_CUR	0x007b	B	0x00	
gas_gauge_BAT_TS_H	0x007c	B	0x00	
gas_gauge_BAT_TS_L	0x007d	B	0x00	
gas_gauge_USB_VOL_H	0x007e	B	0x00	
gas_gauge_USB_VOL_L	0x007f	B	0x00	
gas_gauge_SYS_VOL_H	0x0080	B	0x00	
gas_gauge_SYS_VOL_L	0x0081	B	0x00	
gas_gauge_Q_MAX_H3	0x0082	B	0x00	
gas_gauge_Q_MAX_H2	0x0083	B	0x00	
gas_gauge_Q_MAX_L1	0x0084	B	0x00	
gas_gauge_Q_MAX_L0	0x0085	B	0x00	
gas_gauge_Q_TERM_H3	0x0086	B	0x00	
gas_gauge_Q_TERM_H2	0x0087	B	0x00	
gas_gauge_Q_TERM_L1	0x0088	B	0x00	
gas_gauge_Q_TERM_L0	0x0089	B	0x00	

Name	Offset	Size	Reset Value	Description
gas_gauge_Q_OCV_H3	0x008a	B	0x00	
gas_gauge_Q_OCV_H2	0x008b	B	0x00	
gas_gauge_Q_OCV_L1	0x008c	B	0x00	
gas_gauge_Q_OCV_L0	0x008d	B	0x00	
gas_gauge_OCV_CNT	0x008e	B	0x00	
gas_gauge_SLEEP_CON_SAMP_CUR_H	0x008f	B	0x00	
gas_gauge_SLEEP_CON_SAMP_CUR	0x0090	B	0x60	
gas_gauge_CAL_OFFSET_H	0x0091	B	0x7f	
gas_gauge_CAL_OFFSET_L	0x0092	B	0xff	
gas_gauge_VCALIB0_H	0x0093	B	0x00	
gas_gauge_VCALIB0_L	0x0094	B	0x00	
gas_gauge_VCALIB1_H	0x0095	B	0x00	
gas_gauge_VCALIB1_L	0x0096	B	0x00	
gas_gauge_IOFFSET_H	0x0097	B	0x00	
gas_gauge_IOFFSET_L	0x0098	B	0x00	
gas_gauge_BAT_R0	0x0099	B	0x00	
gas_gauge_BAT_R1	0x009a	B	0x00	
gas_gauge_BAT_R2	0x009b	B	0x00	
gas_gauge_BAT_R3	0x009c	B	0x00	
gas_gauge_DATA0	0x009d	B	0x00	
gas_gauge_DATA1	0x009e	B	0x00	
gas_gauge_DATA2	0x009f	B	0x00	
gas_gauge_DATA3	0x00a0	B	0x00	
gas_gauge_DATA4	0x00a1	B	0x00	
gas_gauge_DATA5	0x00a2	B	0x00	
gas_gauge_DATA6	0x00a3	B	0x00	
gas_gauge_DATA7	0x00a4	B	0x00	
gas_gauge_DATA8	0x00a5	B	0x00	
gas_gauge_DATA9	0x00a6	B	0x00	
gas_gauge_DATA10	0x00a7	B	0x00	
gas_gauge_DATA11	0x00a8	B	0x00	
gas_gauge_VOL_ADC_B3	0x00a9	B	0x00	
gas_gauge_VOL_ADC_B2	0x00aa	B	0x00	
gas_gauge_VOL_ADC_B1	0x00ab	B	0x00	
gas_gauge_VOL_ADC_B_7_0	0x00ac	B	0x00	
gas_gauge_CUR_ADC_K3	0x00ad	B	0x00	
gas_gauge_CUR_ADC_K2	0x00ae	B	0x00	
gas_gauge_CUR_ADC_K1	0x00af	B	0x00	
gas_gauge_CUR_ADC_K0	0x00b0	B	0x00	
PMIC_POWER_EN0	0x00b1	B	0x0f	
PMIC_POWER_EN1	0x00b2	B	0x0f	

Name	Offset	Size	Reset Value	Description
PMIC_POWER_EN2	0x00b3	B	0x06	
PMIC_POWER_EN3	0x00b4	B	0x00	
PMIC_POWER_SLP_EN0	0x00b5	B	0x0f	
PMIC_POWER_SLP_EN1	0x00b6	B	0x6f	
PMIC_POWER_DISCHRG_EN0	0x00b7	B	0xff	
PMIC_POWER_DISCHRG_EN1	0x00b8	B	0xff	
PMIC_POWER_CONFIG	0x00b9	B	0x00	
PMIC_BUCK1_CONFIG	0x00ba	B	0x64	
PMIC_BUCK1_ON_VSEL	0x00bb	B	0x28	
PMIC_BUCK1_SLP_VSEL	0x00bc	B	0x28	
PMIC_BUCK2_CONFIG	0x00bd	B	0x64	
PMIC_BUCK2_ON_VSEL	0x00be	B	0x28	
PMIC_BUCK2_SLP_VSEL	0x00bf	B	0x28	
PMIC_BUCK3_CONFIG	0x00c0	B	0x64	
PMIC_BUCK3_ON_VSEL	0x00c1	B	0x50	
PMIC_BUCK3_SLP_VSEL	0x00c2	B	0x50	
PMIC_BUCK4_CONFIG	0x00c3	B	0x64	
PMIC_BUCK4_ON_VSEL	0x00c4	B	0x62	
PMIC_BUCK4_SLP_VSEL	0x00c5	B	0x62	
PMIC_BUCK4_CMIN	0x00c6	B	0x04	
PMIC_LDO1_ON_VSEL	0x00cc	B	0x6c	
PMIC_LDO1_SLP_VSEL	0x00cd	B	0x6c	
PMIC_LDO2_ON_VSEL	0x00ce	B	0x10	
PMIC_LDO2_SLP_VSEL	0x00cf	B	0x10	
PMIC_LDO3_ON_VSEL	0x00d0	B	0x6c	
PMIC_LDO3_SLP_VSEL	0x00d1	B	0x6c	
PMIC_LDO4_ON_VSEL	0x00d2	B	0x10	
PMIC_LDO4_SLP_VSEL	0x00d3	B	0x10	
PMIC_LDO5_ON_VSEL	0x00d4	B	0x30	
PMIC_LDO5_SLP_VSEL	0x00d5	B	0x30	
PMIC_LDO6_ON_VSEL	0x00d6	B	0x30	
PMIC_LDO6_SLP_VSEL	0x00d7	B	0x30	
PMIC_LDO7_ON_VSEL	0x00d8	B	0x30	
PMIC_LDO7_SLP_VSEL	0x00d9	B	0x30	
PMIC_LDO8_ON_VSEL	0x00da	B	0x6c	
PMIC_LDO8_SLP_VSEL	0x00db	B	0x6c	
PMIC_LDO9_ON_VSEL	0x00dc	B	0x58	
PMIC_LDO9_SLP_VSEL	0x00dd	B	0x58	
PMIC_BOOST_OTG_CONFIG0	0x00de	B	0xb	
PMIC_BOOST_CONFIG1	0x00df	B	0x33	
PMIC_CHRG_OUT	0x00e4	B	0xa2	
PMIC_CHRG_IN	0x00e5	B	0xc8	
PMIC_CHRG_TERM	0x00e6	B	0xc1	

Name	Offset	Size	Reset Value	Description
PMIC_CHRG_TERM_DIG	0x00e7	B	0x00	
PMIC_BATHTS_TS	0x00e8	B	0x00	
PMIC_BATLTS_TS	0x00e9	B	0xff	
PMIC_CHRG_TO	0x00ea	B	0x22	
PMIC_CHRG_STS	0x00eb	B	0x00	
PMIC_BAT_DISCHRG	0x00ec	B	0xa0	
PMIC_CHIP_NAME	0x00ed	B	0x81	
PMIC_CHIP_VER	0x00ee	B	0x72	
PMIC OTP VER	0x00ef	B	0x00	
PMIC_SYS_STS	0x00f0	B	0x00	
PMIC_SYS_CFG0	0x00f1	B	0x84	
PMIC_SYS_CFG1	0x00f2	B	0x80	
PMIC_SYS_CFG2	0x00f3	B	0x00	
PMIC_SYS_CFG3	0x00f4	B	0x20	
PMIC_ON_SOURCE	0x00f5	B	0x00	
PMIC_OFF_SOURCE	0x00f6	B	0x00	
PMIC_PWRON_KEY	0x00f7	B	0x06	
PMIC_INT_STS0	0x00f8	B	0x00	
PMIC_INT_MSK0	0x00f9	B	0x00	
PMIC_INT_STS1	0x00fa	B	0x00	
PMIC_INT_MSK1	0x00fb	B	0x00	
PMIC_INT_STS2	0x00fc	B	0x00	
PMIC_INT_MSK2	0x00fd	B	0x00	
PMIC_GPIO_INT_CONFIG	0x00fe	B	0x22	

Notes: **Size:** **B**- Byte (8 bits) access, **HW**- Half WORD (16 bits) access, **W**-WORD (32 bits) access

## 5.2 Register Description

### RTC\_SECONDS

Address: Operational Base + offset (0x0000)

Bit	Attr	Reset Value	Description
7	RW	0x0	RESV Reserved
6:4	RW	0x0	SEC1 Set the second digit of the RTC seconds (0-5)
3:0	RW	0x0	SEC0 Set the first digit of the RTC seconds (0-9)

### RTC\_MINUTES

Address: Operational Base + offset (0x0001)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	RESV Reserved
6:4	RW	0x0	MIN1 Set the second digit of the RTC minutes (0-5)
3:0	RW	0x0	MIN0 Set the first digit of the RTC minutes (0-9)

**RTC\_HOURS**

Address: Operational Base + offset (0x0002)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	AMPM Only used in PM-AM mode, 1: PM. 0:AM
6	RW	0x0	RESV Reserved
5:4	RW	0x0	HOUR1 Set the second digit of the RTC hours
3:0	RW	0x9	HOUR0 Set the first digit of the RTC hours

**RTC\_DAYS**

Address: Operational Base + offset (0x0003)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:6	RW	0x0	RESV Reserved
5:4	RW	0x0	DAY1 Set the second digit of the RTC days
3:0	RW	0x4	DAY0 Set the first digit of the RTC days

**RTC\_MONTHS**

Address: Operational Base + offset (0x0004)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:5	RW	0x0	RESV Reserved
4	RW	0x0	MONTH1 Set the second digit of the RTC months
3:0	RW	0x8	MONTH0 Set the first digit of the RTC months

**RTC\_YEARS**

Address: Operational Base + offset (0x0005)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:4	RW	0x1	YEAR1 Set the second digit of the RTC years
3:0	RW	0x7	YEAR0 Set the first digit of the RTC years

### RTC\_WEEKS

Address: Operational Base + offset (0x0006)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:3	RW	0x00	RESV Reserved
2:0	RW	0x5	WEEK Set the second digit of the RTC weeks

### RTC\_ALARM\_SECONDS

Address: Operational Base + offset (0x0007)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	RESV Reserved
6:4	RW	0x0	ALARM_SEC1 Set the second digit of the RTC alarm seconds
3:0	RW	0x0	ALARM_SEC0 Set the first digit of the RTC alarm seconds

### RTC\_ALARM\_MINUTES

Address: Operational Base + offset (0x0008)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	RESV Reserved
6:4	RW	0x0	ALARM_MIN1 Set the second digit of the RTC alarm minutes
3:0	RW	0x0	ALARM_MIN0 Set the first digit of the RTC alarm minutes

### RTC\_ALARM\_HOURS

Address: Operational Base + offset (0x0009)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	ALARM_PM_AM Set alarm PM or AM: only used in PM-AM mode, 1: PM. 0:AM
6	RW	0x0	RESV Reserved
5:4	RW	0x0	ALARM_HOUR1 Set the second digit of the RTC alarm hours
3:0	RW	0x0	ALARM_HOUR0 Set the first digit of the RTC alarm hours

**RTC\_ALARM\_DAYS**

Address: Operational Base + offset (0x000a)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:6	RW	0x0	RESV Reserved
5:4	RW	0x0	ALARM_DAY1 Set the second digit of the RTC alarm days
3:0	RW	0x1	ALARM_DAY0 Set the first digit of the RTC alarm days

**RTC\_ALARM\_MONTHS**

Address: Operational Base + offset (0x000b)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:5	RW	0x0	RESV Reserved
4	RW	0x0	ALARM_MONTH1 Set the second digit of the RTC alarm months
3:0	RW	0x1	ALARM_MONTH0 Set the first digit of the RTC alarm months

**RTC\_ALARM\_YEARS**

Address: Operational Base + offset (0x000c)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:4	RW	0x0	ALARM_YEAR1 Set the second digit of the RTC alarm years
3:0	RW	0x0	ALARM_YEAR0 Set the first digit of the RTC alarm years

**RTC\_RTC\_CTRL**

Address: Operational Base + offset (0x000d)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	RTC_READ_SEL 0: Read access directly to dynamic registers 1: Read access to static shadowed registers
6	RW	0x0	GET_TIME Rising transition of this register transferred dynamic registers into static shadowed registers.
5	RW	0x0	SET_32_COUNTER 1: set the 32-kHz counter with COMP_REG value. Note: It must only be used when the RTC is frozen.
4	RW	0x0	RESV Reserved
3	RW	0x0	AMPM_MODE 0: 24 hours mode. 1: 12 hours mode (PM-AM mode)
2	RW	0x0	AUTO_COMP 0: No auto compensation. 1: Auto compensation enabled
1	RW	0x0	ROUND_30S When "1" is written, the time is rounded to the closest minute in next second. Note: self cleared after rounding (Auto Clr)
0	RW	0x0	STOP_RTC 1: RTC is frozen 0: RTC is running. Note: RTC_timecan only be changed during RTC frozen.

**RTC\_RTC\_STATUS**

Address: Operational Base + offset (0x000e)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	W1C	0x1	POWER_UP POWER_UP is set by a reset, is cleared by writing "1" in this bit.
6	W1C	0x0	ALARM Indicates that an alarm interrupt has been generated. Note: The alarm interrupt keeps its low level, until the micro-controller write "1" in the ALARM bit
5	W1C	0x0	EVENT_1D One day has occurred

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
4	W1C	0x0	EVENT_1H One hour has occurred
3	W1C	0x0	EVENT_1M One minute has occurred
2	W1C	0x0	EVENT_1S One second has occurred
1	RO	0x1	RUN 0: RTC is frozen. 1: RTC is running. Note: This bit shows the real state of the RTC.
0	RW	0x0	RESV Reserved

**RTC\_RTC\_INT**

Address: Operational Base + offset (0x000f)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:6	RW	0x0	RESV Reserved
5	RW	0x0	ALARM_EN_PWRON enable the Alarm interrupt to trigger power on. 1: enable; 0: disable
4	RW	0x0	INT_SLEEP_MASK_EN 1: Mask periodic interrupt while the device is in SLEEP mode 0: Normal mode, no interrupt masked.
3	RW	0x0	INT_ALARM_EN Enable one interrupt when the alarm value is reached 1: Enable 0: Disable
2	RW	0x0	INT_TIMER_EN 1: Enable periodic interrupt; 0: disable periodic interrupt
1:0	RW	0x0	EVERY 00: every second; 01: every minute; 10: every hour; 11: every day

**RTC\_RTC\_COMP\_LSB**

Address: Operational Base + offset (0x0010)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	RTC_COMP_LSB This register contains the number of 32-kHz periods to be added into the 32KHz counter every hour [LSB]

**RTC\_RTC\_COMP\_MSB**

Address: Operational Base + offset (0x0011)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	RTC_COMP_MSB This register contains the number of 32-kHz periods to be added into the 32KHz counter every hour [MSB]

**CODEC\_DTOP\_VUCTL**

Address: Operational Base + offset (0x0012)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	ADC_BYPS ADC volume control bypass 0:ADC volume control enable 1: ADC volume control bypass
6	RW	0x0	DAC_BYPS 0:DAC volume control enable 1:DAC volume control bypass
5	RW	0x0	ADCFade ADC Fade: ADC volume adjust mode 0:update to new volume immediately; 1:update volume as ADCZDT field describes;
4	RW	0x0	DACFade DAC Fade: DAC volume adjust mode 0:update to new volume immediately; 1:update volume as DACZDT field describes;
3:2	RW	0x0	RESV Reserved
1	RW	0x1	ADCZDT ADC cross zero detect enable. It works when ADC_BYPS is 0 and ADC_FADE is 1. 0:volume adjusts every sample 1:volume adjusts only when audio waveform crosses zero or volume-control time-limit condition meets; Note: All codec register reset by 'RST'or power down.

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
0	RW	0x1	DACZDT DAC cross zero detect enable. It works when DAC_BYPS is 0 and DAC_FADE is 1. 0:volume adjusts every sample 1:volume adjusts only when audio waveform crosses zero or volume-control time-limit condition meets; Note: All codec register reset by 'RST'or power down.

**CODEC\_DTOP\_VUCTIME**

Address: Operational Base + offset (0x0013)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	VUCT VUCT: volume control time limit, valid only in fade cross zero mode Time limit = VUCT *(1/sample rate) Unit: LRCLK

**CODEC\_DTOP\_LPT\_SRST**

Address: Operational Base + offset (0x0014)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	RESV Reserved
6	RW	0x0	SRST soft reset, write 1 to reset read 1: resetting 0: not resetting
5	RW	0x0	LP_DET LP_DET: low power detected, valid when DAC automatically power-on and power-down enabled 0:not detected; 1:low power detected;
4:0	RW	0x00	LPT LPT: low power detect threshold:power(2,LPT)

**CODEC\_DTOP\_DIGEN\_CLKE**

Address: Operational Base + offset (0x0015)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	ADC_CKE ADC clock enable 1:enable; 0:disable;
6	RW	0x0	I2STX_CKE I2S Tx channel clock enable 1:enable; 0:disable;
5	RW	0x0	ADC_EN Digital adc channel enable 1:enable; 0:disable;
4	RW	0x0	I2STX_EN I2S Tx channel enable 1:enable; 0:disable;
3	RW	0x0	DAC_CKE DAC clock enable 1:enable; 0:disable;
2	RW	0x0	I2SRX_CKE I2S Rx channel clock enable 1:enable; 0:disable;
1	RW	0x0	DAC_EN Digital dac channel enable 1:enable; 0:disable;
0	RW	0x0	I2SRX_EN I2S Rx channel enable 1:enable; 0:disable;

**CODEC\_AREF\_RTCFG1**

Address: Operational Base + offset (0x0017)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	Internal used, don't over write.
6	RW	0x0	LDO1P8A_EN_CODEC Enable the LDO 1P8A, default don't setup. For sleep used only. 0:not effect 1:enable
5	RW	0x0	REF_ADC_SEL Select the ADC reference voltage 0: 1.2V 1: 1.5V
4:3	RW	0x0	VAG_SEL Select the VAG voltage 00:0.9V 01:0.72V 10:1.08V 11:1.26V
2	RW	0x1	PWD_IBIAS Power down the ibias block in REF_TOP 0:IBIAS block power on 1:IBIAS block power down

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
1	RW	0x1	PWD_VAG_BUF Power down the Vag buffer in REF_TOP 0:Vag buffer block power on 1:Vag buffer block power down
0	RW	0x0	RESV Reserved

**CODEC\_AADC\_CFG0**

Address: Operational Base + offset (0x0018)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x1	ADC_L_PWD Power down ADC left channel 0: ADC left channel power on 1: ADC left channel power down
6	RW	0x1	ADC_R_PWD Power down ADC right channel 0: ADC right channel power on 1: ADC right channel power down
5	RW	0x0	ADC_CLK_EDGE_SEL Select the ADC output data and clock edge relationship 0: using the ADC falling edge to send the ADC data 1: using the ADC rising edge to send the ADC data
4	RW	0x0	RESV Reserved
3	RW	0x1	ADC_DITH_OFF Disable the dither function of ADC 0: enable the ADC dither 1:disable the ADC dither
2:0	RW	0x0	ADC_DITH_SEL Select the dither frequency of ADC 000: 1/50 of ADC clock 001: 1/33 of ADC clock 010: 1/20 of ADC clock 011: 1/15 of ADC clock 100: 1/10 of ADC clock 101: 1/8 of ADC clock 110: 1/6 of ADC clock 111: 1/4 of ADC clock

**CODEC\_DADC\_VOLL**

Address: Operational Base + offset (0x001a)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	ADCLV ADC path L-channel Digital Volume Register 0db~ -95db, 0.375db/step 8'h0: 0db 8'h1:-0.375db 8'h2:-0.75db 8'h3:-1.125db ... 8'hff:-95db

### **CODEC\_DADC\_VOLR**

Address: Operational Base + offset (0x001b)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	ADCRV ADC path R-channel Digital Volume Register 0db~ -95db, 0.375db/step 8'h0: 0db 8'h1:-0.375db 8'h2:-0.75db 8'h3:-1.125db ... 8'hff:-95db

### **CODEC\_DADC\_SR\_ACL0**

Address: Operational Base + offset (0x001e)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	ALCL ALC L-channel enable: automatic level control enable for ADC left channel 0: disable 1:enable
6	RW	0x0	ALCR ALC R-channel enable: automatic level control enable for ADC right channel 0: disable 1:enable
5	RW	0x0	ADC_LV_POL ADC path L-channel Digital Volume polarity 0:negative gain; 1:positive gain
4	RW	0x0	ADC_RV_POL ADC path R-channel Digital Volume polarity 0:negative gain; 1:positive gain
3	RW	0x0	RESV Reserved

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
2:0	RW	0x0	ADCSRT ADC sample rate times: sample rate = 8k/11.025k/12k * power(2,ADCSRT) note that sample rate base(8K/11.025K/12K) is decided by PLL configuration.

**CODEC\_DADC\_ALC1**

Address: Operational Base + offset (0x001f)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:4	RW	0x0	ALCARATE ALC attack rate =sample rate/( 8*power(2,ALCARATE))
3:0	RW	0x0	ALCRRATE ALC Release rate=sample rate/( 8*power(2,ALCRRATE))

**CODEC\_DADC\_ALC2**

Address: Operational Base + offset (0x0020)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RO	0x0	NGVALID: noise gate valid status 0:not in NG status;1: now in NG status;
6:4	RW	0x0	ALCMAX The highest threshold of ALC; 000~100:0db~-12db,3db/step; 101~111:-18db~-30db,6db/step;
3	RW	0x0	RESV Reserved
2:0	RW	0x0	ALCMIN The lowest threshold of ALC; 000~100:0db~-12db,3db/step; 101~111:-18db~-30db,6db/step;

**CODEC\_DADC\_NG**

Address: Operational Base + offset (0x0021)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	NGCHL: noise gate channel 0,individual channel(or); 1,both channel(and);

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
6	RW	0x0	NGEN: noise gate enable 0,Noise gate Disable; 1,Noise gate enable;
5	RW	0x0	NGBOOST: noise gate boost 0,Normal noise gate; 1,Boost noise gate;
4:2	RW	0x0	NGGATE: noise gate threshold NGBOOST = 0: 000~111(-63~-84,3db/step) NGBOOST = 1: 000~111(-33~-54,3db/step)
1:0	RW	0x0	NGDLY: noise gate delay The delay time before the noise gate attacks 00~11:2048~4096~8192~16384 samples

**CODEC\_DADC\_HPF**

Address: Operational Base + offset (0x0022)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	HPFL: high pass filter enable for left channel 0:high pass filter for left channel is disabled 1: high pass filter for left channel is enabled
6	RW	0x0	HPFR: high pass filter enable for right channel 0:high pass filter for right channel is disabled 1: high pass filter for right channel is enabled
5:4	RW	0x0	HPF_CF: high pass filter configure register 00:3.79Hz; 01:60Hz; 02:243Hz; 03:493Hz
3:0	RW	0x0	RESV Reserved

**CODEC\_DADC\_RVOLL**

Address: Operational Base + offset (0x0023)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0xff	ADCRLV ADC internal gain of left ch

**CODEC\_DADC\_RVOLR**

Address: Operational Base + offset (0x0024)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0xff	ADCRRV ADC internal gain of right ch

**CODEC\_AMIC\_CFG0**

Address: Operational Base + offset (0x0027)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	MIC_DIFF_EN Enable differential mic mode 0:disable 1:enable
6	RW	0x1	PWD_MIC MIC Power Down 0: MIC block power on 1: MIC block power down
5	RW	0x1	PWD_PGA_L PGA_L Power Down 0:PGA_L block power on 1:PGA_L block power down
4	RW	0x1	PWD_PGA_R PGA_R Power Down 0:PGA_R block power on 1:PGA_R block power down
3:2	RW	0x0	MIC_L_BOOST Select the gain of left mic input signal 00:0dB, 01:10dB 10:20dB 11:30dB
1:0	RW	0x0	MIC_R_BOOST Select the gain of right mic input signal 00:0dB, 01:10dB 10:20dB 11:30dB

### CODEC\_AMIC\_CFG1

Address: Operational Base + offset (0x0028)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	PGA_L_IN_SEL PGA L-channel input select 0: Positive end of Mic amplifier output 1:internal reference voltage
6	RW	0x0	PGA_R_IN_SEL PGA R-channel input select 0: Negative end of Mic amplifier output 1:internal reference voltage
5	RW	0x0	MIC_CHOP_EN Enable the chopping function of MIC 0:disable 1:enable
4	RW	0x0	PGA_CHOP_EN Enable the chopping function of PGA 0:disable 1:enable
3:2	RW	0x0	MIC_CHOP_SEL 00:200k, 01:400k, 10:800k, 11:Reserved
1:0	RW	0x0	PGA_CHOP_SEL 00:200k, 01:400k, 10:800k, 11:Reserved

**CODEC\_DMIC\_PGA\_GAIN**

Address: Operational Base + offset (0x0029)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:4	RW	0x6	PGA_L_GAIN Change the gain of PGA block, the value changed from -18dB to 27dB. 0000:-18db; 1111:27db, 3db/step
3:0	RW	0x6	PGA_R_GAIN Change the gain of PGA block, the value changed from -18dB to 27dB. 0000: -18db; 1111:27db, 3db/step

**CODEC\_DMIC\_LMT1**

Address: Operational Base + offset (0x002a)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	PGA_LMT_EN PGA gain limiter enable 0:disable 1:enable
6:4	RW	0x0	MAX_PGA_LMT The highest threshold of LIMITER; 000~100:0db~-12db,3db/step; 101~111:-18db~-30db,6db/step;
3	RW	0x0	RESV Reserved
2:0	RW	0x0	MIN_PGA_LMT The lowest threshold of LIMITER

**CODEC\_DMIC\_LMT2**

Address: Operational Base + offset (0x002b)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:4	RW	0x0	ATK_RATE_PGA_LMT LIMITER Attack rate=(power(2,ATK_RATE_PGA_LMT)*(8*clk1x)) Clk1x is such as 4.096Mhz,5.6448Mhz,6.144Mhz
3:0	RW	0x0	RLS_RATE_PGA_LMT LIMITER Release rate=(power(2,RLS_RATE_PGA_LMT)*(8*clk1x)) Clk1x is such as 4.096Mhz,5.6448Mhz,6.144Mhz

**CODEC\_DMIC\_NG1**

Address: Operational Base + offset (0x002c)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	NGCHL_LI 0:individual channel; 1:both channel;
6	RW	0x0	NGEN_LI 0:Noise gate Disable; 1:Noise gate enable;
5	RW	0x0	NGBOOST_LI 0:Normal noise gate; 1: Boost noise gate;
4:2	RW	0x0	NGGATE_LI NGBOOST_LI = 0: 000~111(-63~-84,3db/step) NGBOOST_LI = 1: 000~111(-33~-54,3db/step)
1:0	RW	0x0	NGDLY_LI The delay time before the noise gate attacks 00~11:2048~4096~8192~16384, unit: (clk1x * 8)

**CODEC\_DMIC\_NG2**

Address: Operational Base + offset (0x002d)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:1	RO	0x00	RESV Reserved
0	RO	0x0	NGVALID_LI Noise gate valid status

**CODEC\_ADAC\_CFG1**

Address: Operational Base + offset (0x002f)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	DOUBLE_DACIBIAS double DAC internal current resource
6	RW	0x0	INC_DAC_SWITCH increase the DAC internal switch signal control time
5	RW	0x0	STOP_DAC_RSTB stop the RSTB clock
4	RW	0x0	STOP_DAC_SWITCH stop the switch clock in DAC

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
3	RW	0x0	PWD_DACIBIAS power down the DAC internal current resource 0: DACIBIAS powerup 1: DACIBIAS powerdown
2	RW	0x1	PWD_DACD Class D DAC power down 0: Class D DAC power up 1: Class D DAC power down
1	RW	0x1	PWD_DACL L channel DAC power down 0: L channel DAC power up 1: L channel DAC power down
0	RW	0x1	PWD_DACR R channel DAC power down 0: R channel DAC power up 1: R channel DAC power down

**CODEC\_DDAC\_POPD\_DACST**

Address: Operational Base + offset (0x0030)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x1	ATCTRL auto-control power on and power down 0: automatic power control is disabled 1: automatic power control is enabled
6	RW	0x0	RESV Reserved
5	RW	0x0	SMTPO smart power on 0:smart power on is disabled 1:smart power on is enabled
4	RW	0x0	SMTPD smart power down 0:smart power down is disabled 1:smart power down is enabled
3:2	RW	0x0	RESV Reserved
1	RO	0x1	DAC_MTST DAC mute status 0:DAC is not in mute status 1:DAC is in mute status

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
0	RO	0x0	DAC_PWRST DAC power status 0:DAC is powered down 1:DAC is powered on

**CODEC\_DDAC\_VOLL**

Address: Operational Base + offset (0x0031)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	DACLV DAC path L-channel Digital Volume Register 0db~95db, 0.375db/step

**CODEC\_DDAC\_VOLR**

Address: Operational Base + offset (0x0032)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	DACRV DAC path R-channel Digital Volume Register 0db~95db, 0.375db/step

**CODEC\_DDAC\_SR\_LMT0**

Address: Operational Base + offset (0x0035)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	LIMEN LIMITER enable; 0:disable 1:enable
6	RW	0x0	LIMCHL 0:(left+right)/2 1:independent
5	RW	0x0	DAC_LV_POL 0: negative gain; 1:positive gain
4	RW	0x0	DAC_RV_POL 0: negative gain; 1:positive gain
3	RW	0x0	RESV Reserved
2:0	RW	0x0	DACSRT DAC sample rate times sample rate = 8k/11.025k/12k * power(2,DACSRT)

**CODEC\_DDAC\_LMT1**

Address: Operational Base + offset (0x0036)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:4	RW	0x0	LIMRRATE LIMITER Release rate= 8*power(2,LIMRRATE) samples
3:0	RW	0x0	LIMARATE LIMITER attack rate=8*power(2,LIMARATE) samples

**CODEC\_DDAC\_LMT2**

Address: Operational Base + offset (0x0037)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	RESV Reserved
6:4	RW	0x0	LIMMAX The highest threshold of LIMITER; 000~100:0db~-12db,3db/step; 101~111:-18db~-30db,6db/step;
3	RW	0x0	RESV Reserved
2:0	RW	0x0	LIMMIN The lowest threshold of LIMITER;

**CODEC\_DDAC\_MUTE\_MIXCTL**

Address: Operational Base + offset (0x0038)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x1	DAC_D_HPF 0:disable HPF;1:enable HPF;
6:5	RW	0x1	DAC_D_HPF_CF 00:80HZ; 01:100HZ; 02:120HZ; 03:140HZ
4	RW	0x0	CLASS_D_MODE 1:CLASS D mode, 0:L/R mode
3	RW	0x0	CLASSTD_MODE_L_SEL 0: (L+R)/2; 1: L
2	RW	0x0	RESV Reserved
1	RW	0x0	MIX_ON 0:mixer disable;1:enable;
0	RW	0x0	DACMT DAC mute enable 0:DAC mute is disabled 1:DAC mute is enable

**CODEC\_DDAC\_RVOLL**

Address: Operational Base + offset (0x0039)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0xff	DACRLV DAC internal gain of left ch

**CODEC\_DDAC\_RVOLR**

Address: Operational Base + offset (0x003a)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0xff	DACRRV DAC internal gain of right ch

**CODEC\_AHP\_ANTIO**

Address: Operational Base + offset (0x003b)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:5	RW	0x0	RESV Reserved
4:0	RW	0x00	STEP_CTRL STEP_CTRL for HP power on

**CODEC\_AHP\_ANTI1**

Address: Operational Base + offset (0x003c)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:5	RW	0x0	RESV Reserved
4:0	RW	0x00	VOUT_CTRL VOUT_CTRL for HP power on

**CODEC\_AHP\_CFG0**

Address: Operational Base + offset (0x003d)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x1	PWD_SOSTAGE power down the HP SOSTAGE 0:power up 1:power down
6	RW	0x1	PWD_HP_OSTAGE power down the HP OSTAGE 0:power up 1:power down
5	RW	0x1	PWD_HP_BUF power down the HP pre amp stage 0:power up 1:power down
4:3	RW	0x0	INC_HP_AMP increase the HP amplitude from 3dB to 9dB, 00:0db 01:3db 10:6db 11: 9db

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
2	RW	0x0	HP_2STAGE_EN Power down the HP two stage opamp 0:disable 1:enable
1:0	RW	0x0	HP_IBIAS_SEL HP BIAS current select 00:100% 01:150% 10:200% 11:50%

**CODEC\_AHP\_CFG1**

Address: Operational Base + offset (0x003e)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:5	RW	0x0	RESV Reserved
4	RW	0x1	HP_ANTIPOP_EN enable the HP antipop function 0:disable 1:enable
3:0	RW	0xf	HP_ANTIPOP_BIT control the HP antipop gain from -15dB to 0dB 0000: 0dB 0001:-1dB 0010:-2dB ... 1111:-15dB

**CODEC\_AHP\_CP**

Address: Operational Base + offset (0x003f)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:6	RW	0x0	RESV Reserved
5	RW	0x0	HP_CP_CLK_SEL 0: CLK select for head phone charge pump 1MHz :500KHz
4	RW	0x0	HP_CP_EN HP charge pump enable. 0:disable 1:enable
3	RW	0x1	HP_CP_ENDIS_LDO HP charge pump discharge ldo enable 0:disable 1:enable
2	RW	0x0	HP_CP_HIMAXB HP charge pump max current: 0:500mA,1:750mA

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
1:0	RW	0x1	HP_CP_VSEL HP charge pump voltage select: 00:2.1V,01:2.3V,02:2.5V,11:2.7V

**CODEC\_ACCLASSD\_CFG1**

Address: Operational Base + offset (0x0040)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	CLASSD_EN CLASS D enable 0:disable 1:enable
6	RW	0x1	CLASSD_MUTE_EN CLASS D mute_ramp function enable 0:disable 1:enable
5	RW	0x1	CLASSD_SSC_EN CLASS D Spread-Spectrum enable 0:disable 1:enable
4	RW	0x0	CLASSD_SSC_SEL CLASS D Spread-Spectrum steps select 0: 8 steps 1:16 step
3:2	RW	0x2	CLASSD_MUTE_RATE 00:0ms;01:16ms;10:32ms;11:64ms
1:0	RW	0x1	CLASSD_SW_RATE 00:2.5ns;01:5ns;10:7.5ns;11:10ns

**CODEC\_ACCLASSD\_CFG2**

Address: Operational Base + offset (0x0041)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RO	0x0	CLASSD_OCP_STS IF this bit is high, it need to restart CLASS D.
6:4	RW	0x4	CLASSD_OCPP CLASS D PFET OCP Select 000: 0.5A 001: 0.625A 010: 0.75A 011: 0.875A 100:1A (Default) 101: 1.125A 110: 1.25A 111: 1.375A
3	RO	0x0	CLASSD_MUTE_DONE When class d mute finished, this bit will be set high.
2:0	RW	0x4	CLASSD_OCPN CLASS D NFET OCP Select 000: 0.5A 001: 0.625A 010: 0.75A 011: 0.875A 100:1A (Default) 101: 1.125A 110: 1.25A 111: 1.375A

**CODEC\_APLL\_CFG0**

Address: Operational Base + offset (0x0042)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:4	RW	0x0	RESV Reserved
3	RW	0x0	PLL_CLKIN_SEL the PLL input clock select, 0->main clk 1->main clk/2
2	RW	0x1	PLL_OUTDIV_EN enable PLL VCO output clock divide 0:disable 1:enable
1:0	RW	0x0	PLL_VCO_BANDSEL PLL VCO working band select

**CODEC\_APLL\_CFG1**

Address: Operational Base + offset (0x0043)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:6	RW	0x0	PLL_RES_SEL PLL filter resistor value select
5:3	RW	0x0	PLL_CUR_SEL PLL charge-pump working current select
2:0	RW	0x0	PLL_POSDIV_L3 PLL feedback clock divide value select low 3 bits

**CODEC\_APLL\_CFG2**

Address: Operational Base + offset (0x0044)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x30	PLL_POSDIV_H8 PLL feedback clock divide value select high 8 bits

**CODEC\_APLL\_CFG3**

Address: Operational Base + offset (0x0045)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x19	PLL_PREDIV_BIT PLL input clock pre-divide value select

**CODEC\_APLL\_CFG4**

Address: Operational Base + offset (0x0046)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:4	RW	0x6	PLL_OUTDIV PLL VCO output clock divide value select outdiv<3:2>: 00-> divide 5 01-> divide 10 10-> divide 3 11-> divide 6 outdiv<1:0>: 00-> divide 3 01-> divide 1 10-> divide 2 11-> divide 1"
3:0	RW	0x5	PLL_CLK_DIV PLL divided ratio of PLL_HIGH_clk, 0000->divded 1 and 1111->divided 15

**CODEC\_APPL\_CFG5**

Address: Operational Base + offset (0x0047)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:3	RW	0x00	RESV Reserved
2	RW	0x0	PLL_RESET reset the total PLL register 0:release reset 1:set reset
1	RW	0x0	PLL_TEST check the PLL internal VCO control voltage 0:disable 1:enable
0	RW	0x1	PLL_PWD pll power down 0: PLL power up 1:PLL power down

**CODEC\_DI2S\_CKM**

Address: Operational Base + offset (0x0048)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:4	RW	0x0	SCK_DIV $F(mclk2x)/F(sclk) - 1$
3	RW	0x0	PDM_EN I2S SDO output delta-sigma ADC 1bit data. 0:disable; 1:enable.
2	RW	0x0	SCK_EN i2ssclk clock enable, active in master mode. 0:disable 1:enable
1	RW	0x0	SCK_P sclk polarity 0: normal 1:inverted

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
0	RW	0x1	I2S_TX_MST I2S TX module as 0: slave mode 1: master mode

**CODEC\_DI2S\_RSD**

Address: Operational Base + offset (0x0049)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:4	RW	0x0	RESV Reserved
3	RW	0x0	PDM_LR_SEL 0: L; 1: R
2:1	RW	0x0	SCKD_RX sclk divider for rxlrck generator 00:64 01:128 10:256(01 valid only if lrclk<=96k, 10 valid only if lrclk<= 48k)
0	RW	0x0	RXRL_P I2S Rx Irck polarity 0: normal 1:inverted

**CODEC\_DI2S\_RXCR1**

Address: Operational Base + offset (0x004a)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	RESV Reserved
6	RW	0x0	TFS_RX Rx transfer mode selector: 0: I2S 1:PCM
5:4	RW	0x0	PBM_RX Rx PCM bus mode: 00: delay0 01:delay1 10: delay2 11:delay3
3:2	RW	0x0	IBM_RX Rx I2S bus mode: 00: normal 01:left 10:right
1	RW	0x0	EXRL_RX Rx exchange right/left channel for rx 0: normal 1:exchange right and left channel
0	RW	0x0	LSB_RX 0: LSB 1:MSB

**CODEC\_DI2S\_RXCR2**

Address: Operational Base + offset (0x004b)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:5	RW	0x0	RESV Reserved
4:0	RW	0x17	VDW_RX valid date width 0x17: 24 bits data width; 0x0F: 16 bits data width; others: reserved

### **CODEC\_DI2S\_RXCMD\_TSD**

Address: Operational Base + offset (0x004c)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:6	RW	0x0	RESV Reserved
5	RW	0x0	RXS rx transfer start 0: rx stop 1:rx start
4	RW	0x0	RXC rx transfer clear, high active
3	RW	0x0	RESV Reserved
2:1	RW	0x0	SCKD_TX sclk divider for txlrck generator 00:64 01:128 10:256(01 valid only if Irclk<= 96k, 10 valid only if Irclk<= 48k)
0	RW	0x0	TXRL_P I2S Txlrck polarity 0:normal 1:inverted

### **CODEC\_DI2S\_TXCR1**

Address: Operational Base + offset (0x004d)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	RESV Reserved
6	RW	0x0	TFS_TX Tx transfer mode selector: 0: I2S 1:PCM
5:4	RW	0x0	PBM_TX Tx PCM bus mode: 00: delay0 01: delay1 10: delay2

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
3:2	RW	0x0	IBM_TX Tx I2S bus mode: 00: normal 01:left 10:right
1	RW	0x0	EXRL_TX Tx exchange right/left channel for TX 0: normal 1:exchange right and left channel
0	RW	0x0	LSB_TX 0: LSB 1:MSB

**CODEC\_DI2S\_TXCR2**

Address: Operational Base + offset (0x004e)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:5	RW	0x0	RESV Reserved
4:0	RW	0x17	VDW_TX valid date width 0x17: 24 bits data width; 0x0F: 16 bits data width; others: reserved

**CODEC\_DI2S\_TXCR3\_TXCMD**

Address: Operational Base + offset (0x004f)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	TXS tx transfer start 0: tx stop 1:tx start
6	RW	0x0	TXC tx transfer clear, high active
5:0	RW	0x00	RCNT_TX right justified counter for I2S right justified slave mode only

**gas\_gauge\_ADC\_CONFIG0**

Address: Operational Base + offset (0x0050)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x1	GG_EN GG_EN: Gasgauge module enable bit 0:disable 1: enable
6	RW	0x0	SYS_VOL_ADC_EN SYS_VOL_ADC_EN: if GG_EN=0, then the ADC of SYS voltage controlled by the bit 0:disable 1:enable

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
5	RW	0x0	TS_ADC_EN TS_ADC_EN: if GG_EN=0, the ADC of TS1 controlled by the bit 0:disable 1:enable
4	RW	0x0	USB_VOL_ADC_EN USB_VOL_ADC_EN: if GG_EN=0, the ADC of USB voltage by the bit 0:disable 1:enable
3	RW	0x1	BAT_VOL_ADC_EN BAT_VOL_ADC_EN: if GG_EN=0, then the ADC of BAT voltage controlled by the bit 0:disable 1:enable
2	RW	0x1	BAT_CUR_ADC_EN BAT_CUR_ADC_EN: if GG_EN=0, then the ADC of BAT current controlled by the bit 0:disable 1:enable
1	RW	0x0	RESV RESV:Reserve
0	RW	0x0	ADC_SLP_RATE ADC_SLP_RATE: the ADC sample rate: 0:512; 1:1024

**gas\_gauge\_ADC\_CONFIG1**

Address: Operational Base + offset (0x0055)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RC	0x0	VOL_CUR_CALIB_UPD VOL_CUR_CALIB_UPD: The voltage ADC and current ADC calibration finished status 0:not finished 1:finished (Write "1" to clear)
6	RW	0x0	RESV RESV:Reserve
5:4	RW	0x3	VOL_ADC_TSCUR_SEL VOL_ADC_TSCUR_SEL: TS pin flow out current in active state 00:20uA 01:40uA 10:60uA 11:80uA
3	RW	0x0	TS_FUN TS_FUN: TS pin function selection 0:source current to TS pin 1:external voltage input directly
2	RW	0x0	RESV RESV:Reserve

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
1:0	RW	0x0	RLX_CUR_FILTER RLX_CUR_FILTER: Relax mode enter threshold filter. 00:4S; 01:1S; 10:2S; 11:8S;

**gas\_gauge\_GG\_CON**

Address: Operational Base + offset (0x0056)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:6	RW	0x1	RLX_SPT RLX_SPT: relax mode voltage sampling interval time T_RELAX: Relax mode enter and quit time 00:8min 01:16min 10:32min 11:48min
5:4	RW	0x0	ADC_OFF_CAL_INTERV ADC_OFF_CAL_INTERV<1:0>: ADC offset calibration interval time 00:8min 01:16min 10:32min 11:48min
3:2	RW	0x1	FRAME_SMP_INTERV FRAME_SMP_INTERV<1:0>: Data frame sample interval in the sleep state(Unit:S) 00:0S 01:1S 10:2S 11:3S
1	RW	0x0	VOL_OUT_MOD VOL_OUT_MOD: Voltageoutput mode 0:Average Voltage 1:Instant Voltage
0	RW	0x0	CUR_OUT_MOD CUR_OUT_MOD: Current output mode 0:Average Current 1:Instant Current

**gas\_gauge\_GG\_STS**

Address: Operational Base + offset (0x0057)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RO	0x0	OCV_STS OCV_STS: OCV mode status. 1: ocv mode; 0: null ocv mode.
6	RO	0x0	TERM_UPD TERM_UPD: Flag bit for Q_TERM update 0: NOT 1:YES
5	RW	0x0	QMAX_UPD_SOFT QMAX_UPD_SOFT: software Flag bit for QMAX update 0: NOT 1:YES

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
4	RO	0x0	BAT_CON BAT_CON: battery first connection, edge trigger 0:NOT 1:YES
3	RO	0x0	RELAX_VOL1_UPD RELAX_VOL1_UPD: battery voltage1 updated in relax status 0:NOT 1:YES
2	RO	0x0	RELAX_VOL2_UPD RELAX_VOL2_UPD: battery voltage2 updated in relax status 0:NOT 1:YES
1	RO	0x0	RELAX_STS RELAX_STS: battery coming into relax status 0:NOT 1:YES
0	RO	0x0	OCV_UPD OCV_UPD: Flag bit for OCV update 0: NOT 1:YES

**gas\_gauge\_RELAX\_THRE\_H**

Address: Operational Base + offset (0x0058)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	RELAX_THRE_CUR RELAX_THRE_CUR: relax mode threshold current set. <15:8>

**gas\_gauge\_RELAX\_THRE\_L**

Address: Operational Base + offset (0x0059)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x60	RELAX_THRE_CUR RELAX_THRE_CUR: relax mode threshold current set. <7:0>

**gas\_gauge\_RELAX\_VOL1\_H**

Address: Operational Base + offset (0x005a)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	RELAX_VOL1_H RELAX_VOL1_H<15:8>: relax 1st mode voltage

**gas\_gauge\_RELAX\_VOL1\_L**

Address: Operational Base + offset (0x005b)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	RELAX_VOL1_L RELAX_VOL1_L<7:0>: relax 1st mode voltage

**gas\_gauge\_RELAX\_VOL2\_H**

Address: Operational Base + offset (0x005c)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	RELAX_VOL2 RELAX_VOL2<15:8>: relax 2nd mode voltage

**gas\_gauge\_RELAX\_VOL2\_L**

Address: Operational Base + offset (0x005d)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	RELAX_VOL2 RELAX_VOL2<7:0>: relax 2nd mode voltage

**gas\_gauge\_RELAX\_CUR1\_H**

Address: Operational Base + offset (0x005e)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	RELAX_CUR1 RELAX_CUR1<15:8>:relax 1st mode current

**gas\_gauge\_RELAX\_CUR1\_L**

Address: Operational Base + offset (0x005f)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	RELAX_CUR1 RELAX_CUR1<7:0>: relax 1st mode current

**gas\_gauge\_RELAX\_CUR2\_H**

Address: Operational Base + offset (0x0060)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	RELAX_CUR2 RELAX_CUR2<15:8>: relax 2nd mode current

**gas\_gauge\_RELAX\_CUR2\_L**

Address: Operational Base + offset (0x0061)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	RELAX_CUR2 RELAX_CUR2<7:0>: relax 2nd mode current

**gas\_gauge\_OCV\_THRE\_VOL**

Address: Operational Base + offset (0x0062)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	OCV_THRE_VOL OCV_THRE_VOL:OCV mode threshold. 00:0.5mV; 01:1mV; 02:1.5mV.....FF:127.5mV

**gas\_gauge\_OCV\_VOL\_H**

Address: Operational Base + offset (0x0063)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	OCV_VOL_REG OCV_VOL_REG<15:8>: OCV voltage

**gas\_gauge\_OCV\_VOL\_L**

Address: Operational Base + offset (0x0064)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	OCV_VOL_REG OCV_VOL_REG<7:0>:OCV voltage

**gas\_gauge\_OCV\_VOL0\_H**

Address: Operational Base + offset (0x0065)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	OCV_VOL0_REG OCV_VOL0_REG<15:8>:OCV voltage 0

**gas\_gauge\_OCV\_VOL0\_L**

Address: Operational Base + offset (0x0066)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	OCV_VOL0_REG OCV_VOL0_REG<7:0>:OCV voltage 0

**gas\_gauge\_OCV\_CUR\_H**

Address: Operational Base + offset (0x0067)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	OCV_CUR_REG OCV_CUR_REG<15:8>: OCV current

**gas\_gauge\_OCV\_CUR\_L**

Address: Operational Base + offset (0x0068)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	OCV_CUR_REG OCV_CUR_REG<7:0>: OCV current

**gas\_gauge\_OCV\_CUR0\_H**

Address: Operational Base + offset (0x0069)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	OCV_CUR0_REG OCV_CUR0_REG<15:8>: OCV current 0

**gas\_gauge\_OCV\_CUR0\_L**

Address: Operational Base + offset (0x006a)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	OCV_CUR0_REG OCV_CUR0_REG<7:0>: OCV current 0

**gas\_gauge\_PWRON\_VOL\_H**

Address: Operational Base + offset (0x006b)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	PWRON_VOL_REG PWRON_VOL_REG<15:8>: power on bat voltage

**gas\_gauge\_PWRON\_VOL\_L**

Address: Operational Base + offset (0x006c)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	PWRON_VOL_REG PWRON_VOL_REG<7:0>: power on bat voltage

**gas\_gauge\_PWRON\_CUR\_H**

Address: Operational Base + offset (0x006d)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	PWRON_CUR_REG PWRON_CUR_REG<15:8>: power on bat current

**gas\_gauge\_PWRON\_CUR\_L**

Address: Operational Base + offset (0x006e)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	PWRON_CUR_REG PWRON_CUR_REG<7:0>: power on bat current

**gas\_gauge\_OFF\_CNT**

Address: Operational Base + offset (0x006f)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	OFF_CNT OFF_CNT<7:0>: power off time

**gas\_gauge\_Q\_INIT\_H3**

Address: Operational Base + offset (0x0070)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	Q_INIT Q_INIT<31:24>:power off time

**gas\_gauge\_Q\_INIT\_H2**

Address: Operational Base + offset (0x0071)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	Q_INIT Q_INIT<23:16>:power off time

**gas\_gauge\_Q\_INIT\_L1**

Address: Operational Base + offset (0x0072)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	Q_INIT Q_INIT<15:8>:power off time

**gas\_gauge\_Q\_INIT\_L0**

Address: Operational Base + offset (0x0073)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	Q_INIT Q_INIT<7:0>:power off time

**gas\_gauge\_Q\_PRES\_H3**

Address: Operational Base + offset (0x0074)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	Q_PRES Q_PRES<31:24>:Coulomp value

**gas\_gauge\_Q\_PRES\_H2**

Address: Operational Base + offset (0x0075)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	Q_PRES Q_PRES<23:16>:Coulomp value

**gas\_gauge\_Q\_PRES\_L1**

Address: Operational Base + offset (0x0076)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	Q_PRES Q_PRES<15:8>:Coulomp value

**gas\_gauge\_Q\_PRES\_L0**

Address: Operational Base + offset (0x0077)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	Q_PRES Q_PRES<7:0>:Coulomp value

**gas\_gauge\_BAT\_VOL\_H**

Address: Operational Base + offset (0x0078)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	BAT_VOL BAT_VOL<15:8>: bat voltage

**gas\_gauge\_BAT\_VOL\_L**

Address: Operational Base + offset (0x0079)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	BAT_VOL BAT_VOL<7:0>:bat voltage

**gas\_gauge\_BAT\_CUR\_H**

Address: Operational Base + offset (0x007a)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	BAT_CUR BAT_CUR<15:8>:battery current

**gas\_gauge\_BAT\_CUR**

Address: Operational Base + offset (0x007b)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	BAT_CUR BAT_CUR<7:0>:BAT_CUR: battery current

**gas\_gauge\_BAT\_TS\_H**

Address: Operational Base + offset (0x007c)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	BAT_TS BAT_TS<15:8>:TS ADC value

**gas\_gauge\_BAT\_TS\_L**

Address: Operational Base + offset (0x007d)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	BAT_TS BAT_TS<7:0>: TS ADC value

**gas\_gauge\_USB\_VOL\_H**

Address: Operational Base + offset (0x007e)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	USB_VOL USB_VOL<15:8>: USB voltage value

**gas\_gauge\_USB\_VOL\_L**

Address: Operational Base + offset (0x007f)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	USB_VOL USB_VOL<7:0>: USB voltage value

**gas\_gauge\_SYS\_VOL\_H**

Address: Operational Base + offset (0x0080)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	SYS_VOL SYS_VOL<15:8>: SYS voltage value

**gas\_gauge\_SYS\_VOL\_L**

Address: Operational Base + offset (0x0081)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	SYS_VOL SYS_VOL<7:0>: SYS voltage value

**gas\_gauge\_Q\_MAX\_H3**

Address: Operational Base + offset (0x0082)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	Q_MAX Q_MAX<31:24>: Qmax value

**gas\_gauge\_Q\_MAX\_H2**

Address: Operational Base + offset (0x0083)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	Q_MAX Q_MAX<23:16>: Qmax value

**gas\_gauge\_Q\_MAX\_L1**

Address: Operational Base + offset (0x0084)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	Q_MAX Q_MAX<15:8>: Qmax value

**gas\_gauge\_Q\_MAX\_L0**

Address: Operational Base + offset (0x0085)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	Q_MAX Q_MAX<7:0>: Qmax value

**gas\_gauge\_Q\_TERM\_H3**

Address: Operational Base + offset (0x0086)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	Q_TERM Q_TERM<31:24>: charge terminal Coulomb value

**gas\_gauge\_Q\_TERM\_H2**

Address: Operational Base + offset (0x0087)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	Q_TERM Q_TERM<23:16>: charge terminal Coulomp value

**gas\_gauge\_Q\_TERM\_L1**

Address: Operational Base + offset (0x0088)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	Q_TERM Q_TERM<15:8>: charge terminal Coulomp value

**gas\_gauge\_Q\_TERM\_L0**

Address: Operational Base + offset (0x0089)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	Q_TERM Q_TERM<7:0>: charge terminal Coulomp value

**gas\_gauge\_Q\_OCV\_H3**

Address: Operational Base + offset (0x008a)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	Q_OCV Q_OCV<31:24>:OCV update Coulomp value

**gas\_gauge\_Q\_OCV\_H2**

Address: Operational Base + offset (0x008b)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	Q_OCV Q_OCV<23:16>:OCV update Coulomp value

**gas\_gauge\_Q\_OCV\_L1**

Address: Operational Base + offset (0x008c)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	Q_OCV Q_OCV<15:8>:OCV update Coulomp value

**gas\_gauge\_Q\_OCV\_L0**

Address: Operational Base + offset (0x008d)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	Q_OCV Q_OCV<7:0>:OCV update Coulomp value

**gas\_gauge\_OCV\_CNT**

Address: Operational Base + offset (0x008e)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	OCV_CNT OCV_CNT<7:0>: two OCV time interval

**gas\_gauge\_SLEEP\_CON\_SAMP\_CUR\_H**

Address: Operational Base + offset (0x008f)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	SLEEP_CON_SAMP_CUR SLEEP_CON_SAMP_CUR<15:8>:SLEEP mode, When the current is greater than the set value, it is sampled once again, until it is less than the set value, and the value is updated to the RELAX register

**gas\_gauge\_SLEEP\_CON\_SAMP\_CUR**

Address: Operational Base + offset (0x0090)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x60	SLEEP_CON_SAMP_CUR SLEEP_CON_SAMP_CUR<7:0>: SLEEP mode, When the current is greater than the set value, it is sampled once again, until it is less than the set value, and the value is updated to the RELAX register

**gas\_gauge\_CAL\_OFFSET\_H**

Address: Operational Base + offset (0x0091)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x7f	CAL_OFFSET_REG CAL_OFFSET_REG<15:8>: PCB current offset value high bit

**gas\_gauge\_CAL\_OFFSET\_L**

Address: Operational Base + offset (0x0092)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0xff	CAL_OFFSET_REG CAL_OFFSET_REG<7:0>: PCB current offset value low bit

#### **gas\_gauge\_VCALIB0\_H**

Address: Operational Base + offset (0x0093)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	VCALIB0 VCALIB0<15:8>:Voltage0 offset value for AP to calculate offset error and gain error

#### **gas\_gauge\_VCALIB0\_L**

Address: Operational Base + offset (0x0094)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	VCALIB0 VCALIB0<7:0>:Voltage0 offset value for AP to calculate offset error and gain error

#### **gas\_gauge\_VCALIB1\_H**

Address: Operational Base + offset (0x0095)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	VCALIB1 VCALIB1<15:8>:Voltage1 offset value for AP to calculate offset error and gain error

#### **gas\_gauge\_VCALIB1\_L**

Address: Operational Base + offset (0x0096)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	VCALIB1 VCALIB1<7:0>:Voltage1 offset value for AP to calculate offset error and gain error

#### **gas\_gauge\_IOFFSET\_H**

Address: Operational Base + offset (0x0097)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	IOFFSET IOFFSET<15:8>:Current offset value calculated

**gas\_gauge\_IOFFSET\_L**

Address: Operational Base + offset (0x0098)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x00	IOFFSET IOOFFSET<7:0>:Current offset value calculated

**gas\_gauge\_BAT\_R0**

Address: Operational Base + offset (0x0099)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	BAT_R0 BAT_R0<7:0>:BAT resistance

**gas\_gauge\_BAT\_R1**

Address: Operational Base + offset (0x009a)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	BAT_R1 BAT_R1<7:0>:BAT resistance

**gas\_gauge\_BAT\_R2**

Address: Operational Base + offset (0x009b)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	BAT_R2 BAT_R2<7:0>:BAT resistance

**gas\_gauge\_BAT\_R3**

Address: Operational Base + offset (0x009c)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	BAT_R3 BAT_R3<7:0>:BAT resistance

**gas\_gauge\_DATA0**

Address: Operational Base + offset (0x009d)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	DATA DATA<7:0>:data for AP

**gas\_gauge\_DATA1**

Address: Operational Base + offset (0x009e)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	DATA DATA<7:0>:data for AP

#### **gas\_gauge\_DATA2**

Address: Operational Base + offset (0x009f)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	DATA DATA<7:0>:data for AP

#### **gas\_gauge\_DATA3**

Address: Operational Base + offset (0x00a0)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	DATA DATA<7:0>:data for AP

#### **gas\_gauge\_DATA4**

Address: Operational Base + offset (0x00a1)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	DATA DATA<7:0>:data for AP

#### **gas\_gauge\_DATA5**

Address: Operational Base + offset (0x00a2)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	DATA DATA<7:0>:data for AP

#### **gas\_gauge\_DATA6**

Address: Operational Base + offset (0x00a3)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	DATA DATA<7:0>:data for AP

#### **gas\_gauge\_DATA7**

Address: Operational Base + offset (0x00a4)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	DATA DATA<7:0>:data for AP

**gas\_gauge\_DATA8**

Address: Operational Base + offset (0x00a5)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	DATA DATA<7:0>:data for AP

**gas\_gauge\_DATA9**

Address: Operational Base + offset (0x00a6)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	DATA DATA<7:0>:data for AP

**gas\_gauge\_DATA10**

Address: Operational Base + offset (0x00a7)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	DATA DATA<7:0>:data for AP

**gas\_gauge\_DATA11**

Address: Operational Base + offset (0x00a8)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	DATA DATA<7:0>:data for AP

**gas\_gauge\_VOL\_ADC\_B3**

Address: Operational Base + offset (0x00a9)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	OTP	VOL_ADC_B VOL_ADC_B<31:24>: default:OTP

**gas\_gauge\_VOL\_ADC\_B2**

Address: Operational Base + offset (0x00aa)

Register0000 Abstract

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	OTP	VOL_ADC_B VOL_ADC_B<23:16> default: OTP

**gas\_gauge\_VOL\_ADC\_B1**

Address: Operational Base + offset (0x00ab)

Register0000 Abstract

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	OTP	VOL_ADC_B VOL_ADC_B<15:8> default: OTP

**gas\_gauge\_VOL\_ADC\_B\_7\_0**

Address: Operational Base + offset (0x00ac)

Register0000 Abstract

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	OTP	VOL_ADC_B0 VOL_ADC_B<7:0> default: OTP

**gas\_gauge\_CUR\_ADC\_K3**

Address: Operational Base + offset (0x00ad)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	OTP	CUR_ADC_K CUR_ADC_K<31:24> default: OTP

**gas\_gauge\_CUR\_ADC\_K2**

Address: Operational Base + offset (0x00ae)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	OTP	CUR_ADC_K CUR_ADC_K<23:16> default: OTP

**gas\_gauge\_CUR\_ADC\_K1**

Address: Operational Base + offset (0x00af)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	OTP	CUR_ADC_K CUR_ADC_K<15:8> default: OTP

**gas\_gauge\_CUR\_ADC\_K0**

Address: Operational Base + offset (0x00b0)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	OTP	CUR_ADC_K0 CUR_ADC_K<7:0> default: OTP

**PMIC\_POWER\_EN0**

Address: Operational Base + offset (0x00b1)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	BUCK4_EN_MASK BUCK4_EN_MASK: MUST write them to "1" if want to change corresponding BUCK4_EN bit, The BUCK4_EN_MASK bits should be clear when BUCK4_EN bits have been written.
6	RW	0x0	BUCK3_EN_MASK BUCK3_EN_MASK: MUST write them to "1" if want to change corresponding BUCK3_EN bit, The BUCK3_EN_MASK bits should be clear when BUCK3_EN bits have been written.
5	RW	0x0	BUCK2_EN_MASK BUCK2_EN_MASK: MUST write them to "1" if want to change corresponding BUCK2_EN bit, The BUCK2_EN_MASK bits should be clear when BUCK2_EN bits have been written.
4	RW	0x0	BUCK1_EN_MASK BUCK1_EN_MASK: MUST write them to "1" if want to change corresponding BUCK1_EN bit, The BUCK1_EN_MASK bits should be clear when BUCK1_EN bits have been written.
3	RW	OTP	BUCK4_EN BUCK4_EN: BUCK4 enable in active mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.
2	RW	OTP	BUCK3_EN BUCK3_EN: BUCK3 enable in active mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
1	RW	OTP	BUCK2_EN BUCK2_EN: BUCK2 enable in active mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.
0	RW	OTP	BUCK1_EN BUCK1_EN: BUCK1 enable in active mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.

**PMIC\_POWER\_EN1**

Address: Operational Base + offset (0x00b2)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	LDO4_EN_MASK LDO4_EN_MASK: MUST write them to "1" if want to change corresponding LDO4_EN bit, The LDO4_EN_MASK bits should be clear when LDO4_EN bits have been written.
6	RW	0x0	LDO3_EN_MASK LDO3_EN_MASK: MUST write them to "1" if want to change corresponding LDO3_EN bit, The LDO3_EN_MASK bits should be clear when LDO3_EN bits have been written.
5	RW	0x0	LDO2_EN_MASK LDO2_EN_MASK: MUST write them to "1" if want to change corresponding LDO2_EN bit, The LDO2_EN_MASK bits should be clear when LDO2_EN bits have been written.
4	RW	0x0	LDO1_EN_MASK LDO1_EN_MASK: MUST write them to "1" if want to change corresponding LDO1_EN bit, The LDO1_EN_MASK bits should be clear when LDO1_EN bits have been written.
3	RW	OTP	LDO4_EN LDO4_EN: LDO4 enable in active mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
2	RW	OTP	LDO3_EN LDO3_EN: LDO3 enable in active mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.
1	RW	OTP	LDO2_EN LDO2_EN: LDO2 enable in active mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.
0	RW	OTP	LDO1_EN LDO1_EN: LDO1 enable in active mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.

**PMIC\_POWER\_EN2**

Address: Operational Base + offset (0x00b3)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	LDO8_EN_MASK LDO8_EN_MASK: MUST write them to "1" if want to change corresponding LDO8_EN bit, The LDO8_EN_MASK bits should be clear when LDO8_EN bits have been written.
6	RW	0x0	LDO7_EN_MASK LDO7_EN_MASK: MUST write them to "1" if want to change corresponding LDO7_EN bit, The LDO7_EN_MASK bits should be clear when LDO7_EN bits have been written.
5	RW	0x0	LDO6_EN_MASK LDO6_EN_MASK: MUST write them to "1" if want to change corresponding LDO6_EN bit, The LDO6_EN_MASK bits should be clear when LDO6_EN bits have been written.
4	RW	0x0	LDO5_EN_MASK LDO5_EN_MASK: MUST write them to "1" if want to change corresponding LDO5_EN bit, The LDO5_EN_MASK bits should be clear when LDO5_EN bits have been written.

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
3	RW	OTP	LDO8_EN LDO8_EN: LDO8 enable in active mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.
2	RW	OTP	LDO7_EN LDO7_EN: LDO7 enable in active mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.
1	RW	OTP	LDO6_EN LDO6_EN: LDO6 enable in active mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.
0	RW	OTP	LDO5_EN LDO5_EN: LDO5 enable in active mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.

**PMIC\_POWER\_EN3**

Address: Operational Base + offset (0x00b4)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	RESV RESV:Reserve
6	RW	0x0	OTG_EN_MASK OTG_EN _MASK : MUST write them to "1" if want to change corresponding OTG_EN bit, The OTG_EN_MASK bits should be clear when OTG_EN bits have been written.
5	RW	0x0	BOOST_EN_MASK BOOST_EN _MASK : MUST write them to "1" if want to change corresponding BOOST_EN bit, The BOOST_EN_MASK bits should be clear when BOOST_EN bits have been written.

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
4	RW	0x0	LDO9_EN_MASK LDO9_EN_MASK: MUST write them to "1" if want to change corresponding LDO9_EN bit, The LDO9_EN_MASK bits should be clear when LDO9_EN bits have been written.
3	RW	0x0	RESV RESV: Reserve
2	RW	OTP	OTG_EN OTG_EN : OTG enable in active mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.
1	RW	OTP	BOOST_EN BOOST_EN : BOOST enable in active mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.
0	RW	OTP	LDO9_EN LDO9_EN: LDO9 enable in active mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.

**PMIC\_POWER\_SLP\_EN0**

Address: Operational Base + offset (0x00b5)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	RESV RESV: Reserve
6	RW	OTP	OTG_SLP_EN OTG_SLP_EN: OTG enable in SLEEP mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.
5	RW	OTP	BOOST_SLP_EN BOOST_SLP_EN: BOOST enable in SLEEP mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
4	RW	OTP	LDO9_SLP_EN LDO9_SLP_EN: LDO9 enable in SLEEP mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.
3	RW	OTP	BUCK4_SLP_EN BUCK4_SLP_EN: BUCK4 enable in SLEEP mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.
2	RW	OTP	BUCK3_SLP_EN BUCK3_SLP_EN: BUCK3 enable in SLEEP mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.
1	RW	OTP	BUCK2_SLP_EN BUCK2_SLP_EN: BUCK2 enable in SLEEP mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.
0	RW	OTP	BUCK1_SLP_EN BUCK1_SLP_EN: BUCK1 enable in SLEEP mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.

**PMIC\_POWER\_SLP\_EN1**

Address: Operational Base + offset (0x00b6)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	OTP	LDO8_SLP_EN LDO8_SLP_EN: LDO8 enable in SLEEP mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
6	RW	OTP	LDO7_SLP_EN LDO7_SLP_EN: LDO7 enable in SLEEP mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.
5	RW	OTP	LDO6_SLP_EN LDO6_SLP_EN: LDO6 enable in SLEEP mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.
4	RW	OTP	LDO5_SLP_EN LDO5_SLP_EN: LDO5 enable in SLEEP mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.
3	RW	OTP	LDO4_SLP_EN LDO4_SLP_EN: LDO4 enable in SLEEP mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.
2	RW	OTP	LDO3_SLP_EN LDO3_SLP_EN: LDO3 enable in SLEEP mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.
1	RW	OTP	LDO2_SLP_EN LDO2_SLP_EN: LDO2 enable in SLEEP mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.
0	RW	OTP	LDO1_SLP_EN LDO1_SLP_EN: LDO1 enable in SLEEP mode 1, Enable 0, Disable the default value is set by otp reset by power down or RST.

**PMIC\_POWER\_DISCHRG\_EN0**

Address: Operational Base + offset (0x00b7)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x1	RESV RESV:Reserve
6	RW	0x1	OTG_DISCHG_EN OTG_DISCHG_EN: OTG discharge enable when the channel is off 0: Disable 1:enable
5	RW	0x1	RESV RESV:Reserve
4	RW	0x1	LDO9_DISCHG_EN LDO9_DISCHG_EN: LDO9 discharge enable when the channel is off 0: Disable 1:enable
3	RW	0x1	BUCK4_DISCHG_EN BUCK4_DISCHG_EN: BUCK4 discharge enable when the channel is off 0: Disable 1:enable
2	RW	0x1	BUCK3_DISCHG_EN BUCK3_DISCHG_EN: BUCK3 discharge enable when the channel is off 0: Disable 1:enable
1	RW	0x1	BUCK2_DISCHG_EN BUCK2_DISCHG_EN: BUCK2 discharge enable when the channel is off 0: Disable 1:enable
0	RW	0x1	BUCK1_DISCHG_EN BUCK1_DISCHG_EN: BUCK1 discharge enable when the channel is off 0: Disable 1:enable

**PMIC\_POWER\_DISCHRG\_EN1**

Address: Operational Base + offset (0x00b8)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x1	LDO8_DISCHG_EN LDO8_DISCHG_EN: LDO8 discharge enable when the channel is off 0: Disable 1:enable:
6	RW	0x1	LDO7_DISCHG_EN LDO7_DISCHG_EN: LDO7 discharge enable when the channel is off 0: Disable 1:enable:
5	RW	0x1	LDO6_DISCHG_EN LDO6_DISCHG_EN: LDO6 discharge enable when the channel is off 0: Disable 1:enable:

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
4	RW	0x1	LDO5_DISCHG_EN LDO5_DISCHG_EN: LDO5 discharge enable when the channel is off 0: Disable 1:enable:
3	RW	0x1	LDO4_DISCHG_EN LDO4_DISCHG_EN: LDO4 discharge enable when the channel is off 0: Disable 1:enable:
2	RW	0x1	LDO3_DISCHG_EN LDO3_DISCHG_EN: LDO3 discharge enable when the channel is off 0: Disable 1:enable:
1	RW	0x1	LDO2_DISCHG_EN LDO2_DISCHG_EN: LDO2 discharge enable when the channel is off 0: Disable 1:enable:
0	RW	0x1	LDO1_DISCHG_EN LDO1_DISCHG_EN: LDO1 discharge enable when the channel is off 0: Disable 1:enable

**PMIC\_POWER\_CONFIG**

Address: Operational Base + offset (0x00b9)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	LDO_SLP_LP_EN LDO_SLP_LP_EN: Low power function enable bit of LDO 0: disable 1:enable
6	RW	0x0	BUCK3_FB_RES BUCK3_FB_RES: BUCK3 feedback select 0: select external feedback resistor; 1: select internal feedback resistor
5	RW	0x0	BUCK_3VLDO_BYPASS_EN BUCK_3VLDO_BYPASS_EN: 1:3V LDO disable and short to VDD enable bit 0: disable 1:enable
4	RW	0x0	BUCK_3VLDO_LP_EN BUCK_3VLDO_LP_EN: Low power function enable bit of 3VLDO 0: disable 1:enable
3	RW	0x0	BUCK4_LP_EN BUCK4_LP_EN: Low power function enable bit of BUCK4 0: disable 1:enable

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
2	RW	0x0	BUCK3_LP_EN BUCK3_LP_EN: Low power function enable bit of BUCK3 0: disable 1:enable
1	RW	0x0	BUCK2_LP_EN BUCK2_LP_EN: Low power function enable bit of BUCK2 0: disable 1:enable
0	RW	0x0	BUCK1_LP_EN BUCK1_LP_EN: Low power function enable bit of BUCK1 0: disable 1:enable

**PMIC\_BUCK1\_CONFIG**

Address: Operational Base + offset (0x00ba)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:6	RW	0x1	BUCK1_RATE BUCK1_RATE<1:0>: BUCK1 voltage change rate after DVS 00: 3mV/uS; 01: 6.3mV/uS; 10:12.5mV/uS; 11: 25mV/uS reset by power down or RST.
5:3	RW	0x4	BUCK1_ILPK BUCK1_ILPK<2:0>: BUCK1 peak current limit select, MUST linkage adjustment with the BUCK1_ILVL<2:0>(write the same code) 000:2A 010:2.25A 010:2.5A 011:2.75A 100:3A 110:3.25A 110:3.5A 111:3.75A reset by power down or RST.
2:0	RW	0x4	BUCK1_ILVL BUCK1_ILVL<2:0>: BUCK1 valley current limit select, linkage adjustment with the BUCK1_ILPK<2:0>(write the same code) 000:2A 010:2.25A 010:2.5A 011:2.75A 100:3A 110:3.25A 110:3.5A 111:3.75A reset by power down or RST.

**PMIC\_BUCK1\_ON\_VSEL**

Address: Operational Base + offset (0x00bb)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	BUCK1_ON_FPWM BUCK1_ON_FPWM: BUCK1 Forced PWM mode selection 1, Forced PWM mode in active mode; 0, PWM/PFM auto change mode reset by power down or RST.
6:0	RW	OTP	BUCK1_ON_VSEL BUCK1_ON_VSEL<6:0>: BUCK1 active mode voltage select 0000000:0.5V 0000001:0.5125V 0000010:0.525V ... 1010000:1.5V 1010001:1.6V 1010010:1.7V ... 1011000:2.3V 1011001~1111111:2.4V the default value is set by otp reset by power down or RST.

**PMIC\_BUCK1\_SLP\_VSEL**

Address: Operational Base + offset (0x00bc)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	BUCK1_SLP_FPWM BUCK1_SLP_FPWM: 1, Forced PWM mode in sleep mode. 0, PWM/PFM auto change mode. reset by power down or RST.
6:0	RW	OTP	BUCK1_SLP_VSEL BUCK1_SLP_VSEL<6:0>: BUCK1 SLEEP mode voltage select 0000000:0.5V 0000001:0.5125V 0000010:0.525V ... 1010000:1.5V 1010001:1.6V 1010010:1.7V ... 1011000:2.3V 1011001~1111111:2.4V the default value is set byotp reset by power down or RST.

**PMIC\_BUCK2\_CONFIG**

Address: Operational Base + offset (0x00bd)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:6	RW	0x1	BUCK2_RATE BUCK2_RATE<1:0>: BUCK2 voltage change rate after DVS 00: 3mV/uS; 01: 6.3mV/uS; 10:12.5mV/uS; 11: 25mV/uS reset by power down or RST.
5:3	RW	0x4	BUCK2_ILPK BUCK2_ILPK<2:0>: BUCK2 peak current limit select, MUST linkage adjustment with the BUCK2_ILVL<2:0>(write the same code) 000:2A 010:2.25A 010:2.5A 011:2.75A 100:3A 110:3.25A 110:3.5A 111:3.75A reset by power down or RST.
2:0	RW	0x4	BUCK2_ILVL BUCK2_ILVL<2:0>: BUCK2 valley current limit select, linkage adjustment with the BUCK2_ILPK<2:0>(write the same code) 000:2A 010:2.25A 010:2.5A 011:2.75A 100:3A 110:3.25A 110:3.5A 111:3.75A reset by power down or RST.

**PMIC\_BUCK2\_ON\_VSEL**

Address: Operational Base + offset (0x00be)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	BUCK2_ON_FPWM BUCK2_ON_FPWM: BUCK2 Forced PWM mode selection 1, Forced PWM mode in active mode; 0, PWM/PFM auto change mode reset by power down or RST.

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
6:0	RW	OTP	<p>BUCK2_ON_VSEL</p> <p>BUCK2_ON_VSEL&lt;6:0&gt;: BUCK2 active mode voltage select</p> <p>0000000:0.5V</p> <p>0000001:0.5125V</p> <p>0000010:0.525V</p> <p>...</p> <p>1010000:1.5V</p> <p>1010001:1.6V</p> <p>1010010:1.7V</p> <p>...</p> <p>1011000:2.3V</p> <p>1011001~1111111:2.4V</p> <p>the default value is set by otp reset by power down or RST.</p>

**PMIC\_BUCK2\_SLP\_VSEL**

Address: Operational Base + offset (0x00bf)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	<p>BUCK2_SLP_FPWM</p> <p>BUCK2_SLP_FPWM:</p> <p>1, Forced PWM mode in sleep mode.</p> <p>0, PWM/PFM auto change mode.</p> <p>reset by power down or RST.</p>
6:0	RW	OTP	<p>BUCK2_SLP_VSEL</p> <p>BUCK2_SLP_VSEL&lt;6:0&gt;: BUCK2 SLEEP mode voltage select</p> <p>0000000:0.5V</p> <p>0000001:0.5125V</p> <p>0000010:0.525V</p> <p>...</p> <p>1010000:1.5V</p> <p>1010001:1.6V</p> <p>1010010:1.7V</p> <p>...</p> <p>1011000:2.3V</p> <p>1011001~1111111:2.4V</p> <p>the default value is set by otp reset by power down or RST.</p>

**PMIC\_BUCK3\_CONFIG**

Address: Operational Base + offset (0x00c0)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:6	RW	0x1	BUCK3_RATE BUCK3_RATE<1:0>: BUCK3 voltage change rate after DVS 00: 3mV/uS; 01: 6.3mV/uS; 10:12.5mV/uS; 11: 25mV/uS reset by power down or RST.
5:3	RW	0x4	BUCK3_ILPK BUCK3_ILPK<2:0>: BUCK3 peak current limit select, MUST linkage adjustment with the BUCK3_ILVL<2:0>(write the same code) 000:1A 010:1.25A 010:1.5A 011:1.75A 100:2A 110:2.25A 110:2.5A 111:2.75A reset by power down or RST.
2:0	RW	0x4	BUCK3_ILVL BUCK3_ILVL<2:0>: BUCK3 valley current limit select, linkage adjustment with the BUCK3_ILPK<2:0>(write the same code) 000:1A 010:1.25A 010:1.5A 011:1.75A 100:2A 110:2.25A 110:2.5A 111:2.75A reset by power down or RST.

**PMIC\_BUCK3\_ON\_VSEL**

Address: Operational Base + offset (0x00c1)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	BUCK3_ON_FPWM BUCK3_ON_FPWM: BUCK3 Forced PWM mode selection 1, Forced PWM mode in active mode; 0, PWM/PFM auto change mode reset by power down or RST.
6:0	RW	OTP	BUCK3_ON_VSEL BUCK3_ON_VSEL<6:0>: BUCK3 active mode voltage select 0000000:0.5V 0000001:0.5125V 0000010:0.525V ... 1010000:1.5V 1010001:1.6V 1010010:1.7V ... 1011000:2.3V 1011001~1111111:2.4V the default value is set by otp reset by power down or RST.

**PMIC\_BUCK3\_SLP\_VSEL**

Address: Operational Base + offset (0x00c2)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	BUCK3_SLP_FPWM BUCK3_SLP_FPWM: 1, Forced PWM mode in sleep mode. 0, PWM/PFM auto change mode. reset by power down or RST.
6:0	RW	OTP	BUCK3_SLP_VSEL BUCK3_SLP_VSEL<6:0>: BUCK3 SLEEP mode voltage select 0000000:0.5V 0000001:0.5125V 0000010:0.525V ... 1010000:1.5V 1010001:1.6V 1010010:1.7V ... 1011000:2.3V 1011001~1111111:2.4V the default value is set by otp reset by power down or RST.

**PMIC\_BUCK4\_CONFIG**

Address: Operational Base + offset (0x00c3)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:6	RW	0x1	BUCK4_RATE BUCK4_RATE<1:0>: BUCK4 voltage change rate after DVS 00: 3mV/uS; 01: 6.3mV/uS; 10:12.5mV/uS; 11: 25mV/uS reset by power down or RST.
5:3	RW	0x4	BUCK4_ILPK BUCK4_ILPK<2:0>: BUCK4 peak current limit select, MUST linkage adjustment with the BUCK4_ILVL<2:0>(write the same code) 000:1A 010:1.25A 010:1.5A 011:1.75A 100:2A 110:2.25A 110:2.5A 111:2.75A reset by power down or RST.

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
2:0	RW	0x4	BUCK4_ILVL BUCK4_ILVL<2:0>: BUCK4 valley current limit select, linkage adjustment with the BUCK4_ILPK<2:0>(write the same code) 000:1A 010:1.25A 010:1.5A 011:1.75A 100:2A 110:2.25A 110:2.5A 111:2.75A reset by power down or RST.

**PMIC\_BUCK4\_ON\_VSEL**

Address: Operational Base + offset (0x00c4)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	BUCK4_ON_FPWM BUCK4_ON_FPWM: BUCK4 Forced PWM mode selection 1, Forced PWM mode in active mode; 0, PWM/PFM auto change mode reset by power down or RST.
6:0	RW	OTP	BUCK4_ON_VSEL BUCK4_ON_VSEL<6:0>: BUCK4 active mode voltage select 0000000:0.5V 0000001:0.5125V 0000010:0.525V ... 1010000:1.5V 1010001:1.6V 1010010:1.7V ... 1100011~1111111:3.4V the default value is set by otp reset by power down or RST.

**PMIC\_BUCK4\_SLP\_VSEL**

Address: Operational Base + offset (0x00c5)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	BUCK4_SLP_FPWM BUCK4_SLP_FPWM: 1, Forced PWM mode in sleep mode. 0, PWM/PFM auto change mode. reset by power down or RST.

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
6:0	RW	OTP	<p>BUCK4_SLP_VSEL            BUCK4_SLP_VSEL&lt;6:0&gt;: BUCK4 SLEEP mode voltage select            0000000:0.5V            0000001:0.5125V            0000010:0.525V            ...            1010000:1.5V            1010001:1.6V            1010010:1.7V            ...            1100011~1111111:3.4V            the default value is set by otp            reset by power down or RST.</p>

**PMIC\_BUCK4\_CMIN**

Address: Operational Base + offset (0x00c6)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	<p>SYSUV_DLY_SEL            SYSUV_DLY_SEL: Sys under voltage delay time selection 0: 5uS 1:50uS</p>
6	RW	0x0	<p>LDO3_UVSD_EN            LDO3_UVSD_EN: SYSUV to shutdown the LDO3 function            0:Disable 1:enable</p>
5	RW	0x0	<p>SYSUV_TRIG_RESETB_EN            SYSUV_TRIG_RESETB_EN:SYSUV to trigger restart the PMIC function            0:Disable 1:enable</p>
4	RW	0x0	<p>I2S_RX_MST            I2S RX module as master mode(1)/slave mode(0)            reset by power down or RST.</p>
3	RW	0x0	<p>BUCK4_CMIN_EN            BUCK4_CMIN_EN:BUCK4 min Current limit enable            1, Enable            0, Disable            reset by power down or RST.</p>

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
2:1	RW	0x2	BUCK4_CMIN_SEL BUCK4_CMIN_SEL<2:1>: BUCK4 min Current limit select reset by power down or RST. 00:200mA 01:300mA 10:400mA 11:500mA
0	RW	0x0	RESV RESV: Reserve

**PMIC\_LDO1\_ON\_VSEL**

Address: Operational Base + offset (0x00cc)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	LDO1_IMAX LDO1_IMAX:LDO1 current limit setting 0: normal, 1: 130% of nominal value reset by power down or RST.
6:0	RW	OTP	LDO1_ON_VSEL LDO1_ON_VSEL: LDO1 active mode voltage select, 0.6V~3.4V(step=25mV) 0000000:0.6V 0000001:0.625V 0000010:0.65V ... 1110000~1111111:3.4V the default value is set by otp reset by power down or RST.

**PMIC\_LDO1\_SLP\_VSEL**

Address: Operational Base + offset (0x00cd)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	RESV RESV:Reserve
6:0	RW	OTP	LDO1_SLP_VSEL LDO1_SLP_VSEL:LDO1 SLEEP mode voltage select, 0.6V~3.4V(step=25mV) 0000000:0.6V 0000001:0.625V 0000010:0.65V ... 1110000~1111111:3.4V the default value is set by otp reset by power down or RST.

**PMIC\_LDO2\_ON\_VSEL**

Address: Operational Base + offset (0x00ce)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	LDO2_IMAX LDO2_IMAX:LDO2 current limit setting 0: normal, 1: 130% of nominal value reset by power down or RST.
6:0	RW	OTP	LDO2_ON_VSEL LDO2_ON_VSEL: LDO2 active mode voltage select, 0.6V~3.4V(step=25mV) 0000000:0.6V 0000001:0.625V 0000010:0.65V ... 1110000~1111111:3.4V the default value is set by otp reset by power down or RST.

**PMIC\_LDO2\_SLP\_VSEL**

Address: Operational Base + offset (0x00cf)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	RESV RESV:Reserve
6:0	RW	OTP	LDO2_SLP_VSEL LDO2_SLP_VSEL:LDO2 SLEEP mode voltage select, 0.6V~3.4V(step=25mV) 0000000:0.6V 0000001:0.625V 0000010:0.65V ... 1110000~1111111:3.4V the default value is set by otp reset by power down or RST.

**PMIC\_LDO3\_ON\_VSEL**

Address: Operational Base + offset (0x00d0)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	LDO3_IMAX LDO3_IMAX:LDO3 current limit setting 0: normal, 1: 130% of nominal value reset by power down or RST.

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
6:0	RW	OTP	<p>LDO3_ON_VSEL  LDO3_ON_VSEL: LDO3 active mode voltage select, 0.6V~3.4V(step=25mV)  0000000:0.6V  0000001:0.625V  0000010:0.65V  ...  1110000~1111111:3.4V  the default value is set by otp reset by power down or RST.</p>

**PMIC\_LDO3\_SLP\_VSEL**

Address: Operational Base + offset (0x00d1)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	<p>RESV  RESV:Reserve</p>
6:0	RW	OTP	<p>LDO3_SLP_VSEL  LDO3_SLP_VSEL:LDO3 SLEEP mode voltage select, 0.6V~3.4V(step=25mV)  0000000:0.6V  0000001:0.625V  0000010:0.65V  ...  1110000~1111111:3.4V  the default value is set by otp reset by power down or RST.</p>

**PMIC\_LDO4\_ON\_VSEL**

Address: Operational Base + offset (0x00d2)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	<p>LDO4_IMAX  LDO4_IMAX:LDO4 current limit setting  0: normal,  1: 130% of nominal value  reset by power down or RST.</p>

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
6:0	RW	OTP	<p>LDO4_ON_VSEL  LDO4_ON_VSEL: LDO4 active mode voltage select, 0.6V~3.4V(step=25mV)  0000000:0.6V  0000001:0.625V  0000010:0.65V  ...  1110000~1111111:3.4V  the default value is set by otp reset by power down or RST.</p>

**PMIC\_LDO4\_SLP\_VSEL**

Address: Operational Base + offset (0x00d3)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	<p>RESV  RESV:Reserve</p>
6:0	RW	OTP	<p>LDO4_SLP_VSEL  LDO4_SLP_VSEL:LDO4 SLEEP mode voltage select, 0.6V~3.4V(step=25mV)  0000000:0.6V  0000001:0.625V  0000010:0.65V  ...  1110000~1111111:3.4V  the default value is set by otp reset by power down or RST.</p>

**PMIC\_LDO5\_ON\_VSEL**

Address: Operational Base + offset (0x00d4)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	<p>LDO5_IMAX  LDO5_IMAX:LDO5current limit setting  0: normal,  1: 130% of nominal value  reset by power down or RST.</p>

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
6:0	RW	OTP	<p>LDO5_ON_VSEL  LDO5_ON_VSEL: LDO5 active mode voltage select, 0.6V~3.4V(step=25mV)  0000000:0.6V  0000001:0.625V  0000010:0.65V  ...  1110000~1111111:3.4V  the default value is set by otp reset by power down or RST.</p>

**PMIC\_LDO5\_SLP\_VSEL**

Address: Operational Base + offset (0x00d5)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	<p>RESV  RESV:Reserve</p>
6:0	RW	OTP	<p>LDO5_SLP_VSEL  LDO5_SLP_VSEL:LDO5 SLEEP mode voltage select, 0.6V~3.4V(step=25mV)  0000000:0.6V  0000001:0.625V  0000010:0.65V  ...  1110000~1111111:3.4V  the default value is set by otp reset by power down or RST.</p>

**PMIC\_LDO6\_ON\_VSEL**

Address: Operational Base + offset (0x00d6)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	<p>LDO6_IMAX  LDO6_IMAX:LDO6 current limit setting  0: normal,  1: 130% of nominal value  reset by power down or RST.</p>

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
6:0	RW	OTP	<p>LDO6_ON_VSEL  LDO6_ON_VSEL: LDO6 active mode voltage select, 0.6V~3.4V(step=25mV)  0000000:0.6V  0000001:0.625V  0000010:0.65V  ...  1110000~1111111:3.4V  the default value is set by otp  reset by power down or RST.</p>

**PMIC\_LDO6\_SLP\_VSEL**

Address: Operational Base + offset (0x00d7)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	<p>RESV  RESV:Reserve</p>
6:0	RW	OTP	<p>LDO6_SLP_VSEL  LDO6_SLP_VSEL:LDO6 SLEEP mode voltage select, 0.6V~3.4V(step=25mV)  0000000:0.6V  0000001:0.625V  0000010:0.65V  ...  1110000~1111111:3.4V  the default value is set by otp  reset by power down or RST.</p>

**PMIC\_LDO7\_ON\_VSEL**

Address: Operational Base + offset (0x00d8)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	<p>LDO7_IMAX  Field0000 Abstract  LDO7_IMAX:LDO7 current limit setting  0: normal,  1: 130% of nominal value  reset by power down or RST.</p>

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
6:0	RW	OTP	<p>LDO7_ON_VSEL  LDO7_ON_VSEL: LDO7 active mode voltage select, 0.6V~3.4V(step=25mV)  0000000:0.6V  0000001:0.625V  0000010:0.65V  ...  1110000~1111111:3.4V  the default value is set by otp reset by power down or RST.</p>

**PMIC\_LDO7\_SLP\_VSEL**

Address: Operational Base + offset (0x00d9)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	<p>RESV  RESV:Reserve</p>
6:0	RW	OTP	<p>LDO7_SLP_VSEL  LDO7_SLP_VSEL:LDO7 SLEEP mode voltage select, 0.6V~3.4V(step=25mV)  0000000:0.6V  0000001:0.625V  0000010:0.65V  ...  1110000~1111111:3.4V  the default value is set by otp reset by power down or RST.</p>

**PMIC\_LDO8\_ON\_VSEL**

Address: Operational Base + offset (0x00da)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	<p>LDO8_IMAX  LDO8_IMAX:LDO8 current limit setting  0: normal,  1: 130% of nominal value  reset by power down or RST.</p>

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
6:0	RW	OTP	<p>LDO8_ON_VSEL Field0000 Abstract LDO8_ON_VSEL: LDO8 active mode voltage select, 0.6V~3.4V(step=25mV) 0000000:0.6V 0000001:0.625V 0000010:0.65V ... 1110000~1111111:3.4V the default value is set by otp reset by power down or RST.</p>

**PMIC\_LDO8\_SLP\_VSEL**

Address: Operational Base + offset (0x00db)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	<p>RESV RESV:Reserve</p>
6:0	RW	OTP	<p>LDO8_SLP_VSEL LDO8_SLP_VSEL:LDO8 SLEEP mode voltage select, 0.6V~3.4V(step=25mV) 0000000:0.6V 0000001:0.625V 0000010:0.65V ... 1110000~1111111:3.4V the default value is set by otp reset by power down or RST.</p>

**PMIC\_LDO9\_ON\_VSEL**

Address: Operational Base + offset (0x00dc)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	<p>LDO9_IMAX LDO9_IMAX:LDO9 current limit setting 0: normal, 1: 130% of nominal value reset by power down or RST.</p>

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
6:0	RW	OTP	<p>LDO9_ON_VSEL LDO9_ON_VSEL: LDO9 active mode voltage select, 0.6V~3.4V(step=25mV) 0000000:0.6V 0000001:0.625V 0000010:0.65V ... 1110000~1111111:3.4V the default value is set by otp reset by power down or RST.</p>

**PMIC\_LDO9\_SLP\_VSEL**

Address: Operational Base + offset (0x00dd)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	<p>RESV RESV:Reserve</p>
6:0	RW	OTP	<p>LDO9_SLP_VSEL LDO9_SLP_VSEL:LDO9 SLEEP mode voltage select, 0.6V~3.4V(step=25mV) 0000000:0.6V 0000001:0.625V 0000010:0.65V ... 1110000~1111111:3.4V the default value is set by otp reset by power down or RST.</p>

**PMIC\_BOOST\_OTG\_CONFIG0**

Address: Operational Base + offset (0x00de)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:6	RW	0x0	<p>OTG_ILIM OTG_ILIM: OTG current limit selection 00: 1A 01:1.5A 10:1.8A 11: 2.1A reset by power down or RST.</p>
5	RW	0x0	<p>RESV Reserved</p>
4:3	RW	0x1	<p>BOOST_ILMAX BOOST_ILMAX:BOOST inductor peak current setting 00:2.5A 01:3A 10:4A 11:5A reset by power down or RST.</p>

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
2:0	RW	OTP	BOOST_ON_VSEL BOOST_ON_VSEL:BOOST active mode voltage select. 000:4.7V 001:4.8V 010:4.9V 011:5V 100:5.1V 101:5.2V 110:5.3V 111:5.4V the default value is set by otp reset by power down or RST.

**PMIC\_BOOST\_CONFIG1**

Address: Operational Base + offset (0x00df)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:5	RW	0x1	RESV Reserved
4:3	RW	0x2	BOOST_ZCD BOOST_ZCD<1:0>: BOOSTzero current detection select 00:50mA 01: 100mA 10:150mA 11:200mA
2:0	RW	OTP	BOOST_SLP_VSEL BOOST_SLP_VSEL:BOOST SLEEP mode voltage select. 000: 4.7V; 001: 4.8V; 010: 4.9V; 011: 5.0V 100: 5.1V; 101: 5.2V; 110: 5.3V; 111: 5.4V the default value is set by otp reset by power down or RST.

**PMIC\_CHRG\_OUT**

Address: Operational Base + offset (0x00e4)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x1	POWERPATH_EN PWOERPATH_EN: PWOERPATH enable signal 0:disable 1: enable
6:4	RW	0x2	CHRG_VOL_SEL CHRG_VOL_SEL: charger voltage selection 000:4.1V 001:4.15V 010:4.2V 011:4.25V 100:4.3V 101:4.35; 110:4.4V; 111:4.45V
3	RW	0x0	CHRG_CT_EN CHRG_CT_EN:Charger Thermal foldback enable 0:disable 1:enable
2:0	RW	0x2	CHRG_CUR_SEL CHRG_CUR_SEL: charger current selection 000:1A 001:1.5A 010:2A 011:2.5A 100:2.75A 101:3A 110:3.5A 111:0.5A

**PMIC\_CHRG\_IN**

Address: Operational Base + offset (0x00e5)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x1	USB_VLIM_EN USB_VLIM_EN: whether the USB input voltage limit function is enable 0:disable 1: enable
6:4	RW	0x4	USB_VLIM_SEL USB_VLIM_SEL: the USB input voltage limit selection 000:4.0V 001:4.1V 010:4.2V 011:4.3V 100:4.4V 101:4.5V 110:4.6V 111:4.7V
3	RW	0x1	USB_ILIM_EN USB_ILIM_EN: whether the USB input current limit function is enable 0:disable 1: enable
2:0	RW	OTP	USB_ILIM_SEL USB_ILIM_SEL: the USB input average current limit selection 000:0.45 001:0.08A 010:0.85A 011:1.5A 100:1.75A 101:2A 110:2.5A 111:3A the default value is set by OTP.

**PMIC\_CHRG\_TERM**

Address: Operational Base + offset (0x00e6)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x1	SYS_CAN_SD SYS_CAN_SD:whether the system voltage can be shutdown in Bat_off mode 0:not 1:yes
6	RW	0x1	CHRG_EN CHRG_EN: enable charger 0:disable 1:enable reset by power down or RST.
5:4	RW	0x0	RESV RESV:Reserve
3	RW	0x0	BAT_OVP_EN BAT_OVP_EN: BAT OVP ENABLE 0:disable 1: enable
2	RW	0x1	CHRG_TERM_ANA_DIG CHRG_TERM_ANA_DIG:charger termination adjustment selection 0: analog 1:digital

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
1:0	RW	0x1	CHRG_TERM_ANA_SEL CHRG_TERM_ANA_SEL: analog charging termination selection 00:150mA 01:200mA 10:300mA 11:400mA

**PMIC\_CHRG\_TERM\_DIG**

Address: Operational Base + offset (0x00e7)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x20	CHRG_TERM_DIG CHRG_TERM_DIG: CHRG TERM DIGITAL CURRENT SELLECT Compared with BAT_CUR<12:5>

**PMIC\_BATHTS\_TS**

Address: Operational Base + offset (0x00e8)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0x00	BATHTS_TS BATHTS_TS: battery high temperature protection in TS according to ADC SPEC, high 8bit of ADC value, the external resistor is negative temperature coefficient, so BATHTS_TS<BAT LTS_TS

**PMIC\_BATLTS\_TS**

Address: Operational Base + offset (0x00e9)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RW	0xff	BATLTS_TS BATLTS_TS: battery low temperature protection in TS according to ADC SPEC,high 8bit of ADC value, the external resistor is negative temperature coefficient, so BATHTS_TS<BAT LTS_TS

**PMIC\_CHRG\_TO**

Address: Operational Base + offset (0x00ea)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	CHRG_TIMER_TRIKL_EN CHRG_TIMER_TRIKL_EN: trickle charging timer enable, 0:disable 1:enable
6:4	RW	0x2	CHRG_TIMER_TRIKL CHRG_TIMER_TRIKL: trickle charge timer selection 000:30min 001:45min 010:60min 011:90min 100:120min 101:150min 110:180min 111:210min
3	RW	0x0	CHRG_TIMER_CCCV_EN CHRG_TIMER_CCCV_EN: Constant current and Constant voltage charging timer enable, 0:disable 1:enable
2:0	RW	0x2	CHRG_TIMER_CCCV CHRG_TIMER_CCCV:CC CV charge timer selection 000:4h 001:5h 010:6h 011:8h 100:10h 101:12h 110:14h 111:16h

**PMIC\_CHRG\_STS**

Address: Operational Base + offset (0x00eb)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RO	0x0	BAT_EXS BAT_EXS:bat exists (only writable at test mode) 0:Not exists 1:exists
6:4	RO	0x0	CHG_STS CHG_STS: charging status 000: charge off 001:dead charge 010:trickle charge 011: CC or CV charge 100:charge TERM 101:USB over voltage 110:BAT temperature error 111:BAT time error
3	RO	0x0	BAT_OVP_STS BAT_OVP_STS:BAT OVP happen, this bit will be set high.
2	RO	0x0	CHRG_IN_CLAMP CHRG_IN_CLAMP: When charger incc, incv or constant temperature happen, this bit will be set "1"

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
1	RO	0x0	USB_EXS USB_EXS:USB exists (only writable at test mode) 0: Not exists, 1: exists
0	RO	0x0	USB_EFF USB_EFF:USB is effective (only writable at test mode) 0: Not effective, 1: effective

**PMIC\_BAT\_DISCHRG**

Address: Operational Base + offset (0x00ec)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	RESV RESV:Reserve
6	RO	0x0	BAT_DIS_ILIM_STS BAT_DIS_ILIM_STS:When bat discharge current is limited, this bit will be set high.
5:4	RW	0x0	BAT_SYS_CMP_DLY BAT_SYS_CMP_DLY:bat and system comparator delay time 00:5uS 10:10uS 01:25uS 11:30uS
3	RW	0x1	BAT_DIS_ILIM_EN BAT_DIS_ILIM_EN:the bat discharger current limit function enable 0:disable 1:enable
2:0	RW	0x2	BAT_DISCHRG_ILIM BAT_DISCHRG_ILIM:battery discharge current limit 000:2A 001:2.5A 010:3A 011 3.5A 1xx:4A

**PMIC\_CHIP\_NAME**

Address: Operational Base + offset (0x00ed)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:0	RO	0x81	CHIP_NAME CHIP_NAME:CHIP name code<11:4>. RK817: default 81

**PMIC\_CHIP\_VER**

Address: Operational Base + offset (0x00ee)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:4	RO	0x7	CHIP_NAME CHIP_NAME:CHIP name code<3:0>. RK817: default 7
3:0	RO	0x2	CHIP_VER CHIP_VER:CHIP version code<3:0>, from 1 to 15.

**PMIC OTP VER**

Address: Operational Base + offset (0x00ef)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:6	RW	0x0	LDO1P8A_VSEL LDO1P8A_VSEL: VCC_1P8A voltage select 00: 1.8V 01: 1.6V 10: 1.9V 11:2.0V
5:4	RO	0x0	RESV RESV:Reserve
3:0	RO	OTP	OTP_VER OTP_VER: OTP revize version. default OTP.

**PMIC\_SYS\_STS**

Address: Operational Base + offset (0x00f0)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RO	0x0	PWRON_STS PWRON_STS: PWRON key status 0: PWRON not press 1:PWRON button pressed reset by power down or RST
6	RO	0x0	PLUG_IN_STS PLUG_IN_STS: USB plug-in event occurs(USB voltage >3.8V after pull down 20mA current) 0: no USB plug in 1: USB plugged in
5	RO	0x0	VB_UV_STS VB_UV_STS: Battery under voltage lockout status
4	RO	0x0	VB_LO_STS VB_LO_STS: Battery low voltage status 0: VBAT>VB_LO_SEL 1: VBAT<VB_LO_SEL
3	RO	0x0	HOTDIE_STS HOTDIE_STS: Hot-die warning

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
2	RO	0x0	TSD_STS TSD_STS: Thermal shut down
1	RO	0x0	BAT_HI_STS BAT_HI_STS: battery higher than USB status bit
0	RO	0x0	SYS_OV_STS SYS_OV_STS: system over voltage status bit

**PMIC\_SYS\_CFG0**

Address: Operational Base + offset (0x00f1)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x1	SYS_OV_EN SYS_OV_EN: SYS over voltage function enable 0:disable 1:enable
6:4	RW	0x0	VB_UV_SEL VB_UV_SEL: SYS shut down voltage select, 2.7V~3.4V, step=100mV 000:2.7V; 001:2.8V; 010:2.9V; 011:3.0V 100:3.1V; 101:3.2V; 110:3.3V; 111:3.4V reset by power down or RST
3	RW	0x1	VB_LO_ACT VB_LO_ACT: SYS low voltage action 0: shut down system 1: insert interrupt reset by power down or RST
2:0	RW	0x4	VB_LO_SEL VB_LO_SEL: SYS low voltage threshold, 2.8V~3.5V, step=100mV 000:2.8V; 001:2.9V; 010:3.0V; 011:3.1V 100:3.2V; 101:3.3V; 110:3.4V; 111:3.5V reset by power down or RST

**PMIC\_SYS\_CFG1**

Address: Operational Base + offset (0x00f2)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x1	CLK32KOUT_EN CLK32KOUT_EN: CLK32K output is enable 1. enable 0. disable reset by power down or RST

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
6	RW	0x0	TSD_TEMP TSD_TEMP: Thermal shutdown temperature threshold 0: 140°C; 1: 160°C reset by power down or RST
5:4	RW	0x0	HOTDIE_TEMP HOTDIE_TEMP: Hot-die temperature threshold 00:85°C 01:95°C 10:105°C 11:115°C reset by power down or RST
3	RW	0x0	SYS_OV_SD_EN SYS_OV_SD_EN: Shut down the BUCK1~4 mosfet if the SYS OV happens 0:Disable 1:Enable
2	RW	0x0	SYS_OV_SD_TIME SYS_OV_SD_TIME: SYS OV comparator delay time selection 0: 8uS 1:30uS
1	RW	0x0	USB_OV_SD_EN USB_OV_SD_EN: Shut down the charger mosfet if the USB OV happens 0:Disable 1:Enable
0	RW	0x0	USB_OV_SD_TIME USB_OV_SD_TIME: USB OV comparator delay time selection 0: 8uS 1:60uS

**PMIC\_SYS\_CFG2**

Address: Operational Base + offset (0x00f3)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	ADC_PHASE ADC_PHASE: ADC phase select 0: normal 1: reverse
6	RW	0x1	CHRG_CLK_SEL CHRG_CLK_SEL: charger clock select 0:1Meg 1:2Meg
5	RW	0x0	HK_BG_SUP_SEL HK_BG_SUP_SEL: house keeping band gap supply select 0:VCCRTC 1: Internal LDO

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
4	RW	0x0	HK_REF_RES_SEL HK_REF_RES_SEL: house keeping reference filter resistor select 0:100% 1:200%
3	RW	0x0	HK_REF_LP_EN HK_REF_LP_EN: house keeping reference lower power enable 1. enable 0. disable
2	RW	0x0	USB_OV_SEL USB_OV_SEL: usb over voltage threshold select 0: 6V 1: 5.8V
1	RW	0x0	SYS_UV_PRE_DLY SYS_UV_PRE_DLY: SYS under voltage delay time select 0:1.5uS 1:5uS
0	RW	0x0	USB_OV_DLY USB_OV_DLY: usb over voltage delay time select 0: 5uS 1:3uS

**PMIC\_SYS\_CFG3**

Address: Operational Base + offset (0x00f4)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7:6	RW	0x0	RST_FUN: reset function selection: 00: Restart the PMU. 01: reset DCDC and LDO. (Do not use this mode when SLEEP.) 1x: Do not use.
5	RW	0x1	SLP_POL SLP_POL: SLEEP pin polarity 0:active low 1:active high reset by power down or RST

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
4:3	RW	0x0	SLP_FUN SLP_FUN: SLEEP PIN function selection: 00: not effect; 01: sleep function; 10:shutdown function; 11:restart pmu function. reset by power down or RST
2	RW	0x0	DEV_RST DEV_RST: Write 1 will 'RST' the device. Note: 'RST' is not only a reset source, but a special function defined by 'RST_FUN' reset by power down or RST
1	RW	0x0	DEV_SLP DEV_SLP: Write 1 will go to SLEEP state. reset by power down or RST
0	RW	0x0	DEV_OFF DEV_OFF: Write 1 will shutdown the device. reset by power down or RST

**PMIC\_ON\_SOURCE**

Address: Operational Base + offset (0x00f5)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RO	0x0	ON_PWRON ON_PWRON: PRESS PWRON to turn on PMU reset by power down or RST, and load this bit after reset.
6	RO	0x0	ON_PLUG_IN ON_PLUG_IN:USB PLUG IN to turn on PMU reset by power down or RST
5	RO	0x0	ON_RTC ON_RTC:RTC timer to turn on PMU reset by power down or RST
4	RO	0x0	RESTART_RESETB RESTART_RESETB:PULL LOW the RESETB PIN to restart the PMU reset by power down or RST
3	RO	0x0	RESTART_PWRON_LP RESTART_PWRON_LP:Long press PWRON to restart the PMU reset by power down or RST
2	RO	0x0	RESTART_SLP RESTART_SLP:SLEEP PIN ACTIVE to restart the PMU reset by power down or RST

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
1	RW	0x0	RESTART_DEV_RST RESTART_DEV_RST: I2C write DEV_RST to restart PMU reset by power down or RST
0	RO	0x0	RESV RESV: Reserve

**PMIC\_OFF\_SOURCE**

Address: Operational Base + offset (0x00f6)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RO	0x0	OFF_SLP OFF_SLP: SLEEP PIN ACTIVE to turn off PMU reset by power down or RST, and load this bit after reset.
6	RO	0x0	OFF_SYS_OV OFF_SYS_OV:SYS OV to turn off PMU reset by power down or RST, and load this bit after reset.
5	RO	0x0	OFF_TSD OFF_TSD:TSD to turn off PMU reset by power down or RST, and load this bit after reset.
4	RO	0x0	OFF_VB_UV OFF_VB_UV:SYS UV to turn off PMU reset by power down or RST, and load this bit after reset.
3	RO	0x0	OFF_DEV_OFF OFF_DEV_OFF:I2C write DEV_OFF to turn off PMU reset by power down or RST, and load this bit after reset.
2	RO	0x0	OFF_PWRON_LP OFF_PWRON_LP:long press PWRON to turn off PMU reset by power down or RST, and load this bit after reset.
1	RO	0x0	OFF_USB_EFF_NOT OFF_USB_EFF_NOT: USB OV or UV to turn off PMU when BUCK MODE reset by power down or RST, and load this bit after reset.

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
0	RO	0x0	OFF_VB_LO OFF_VB_LO:SYS Low (if VB_LO_ACT=0)to turn off PMU reset by power down or RST, and load this bit after reset.

**PMIC\_PWRON\_KEY**

Address: Operational Base + offset (0x00f7)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	OTP	PWRON_ON_TIME PWRON_ON_TIME:0:500mS; 1:100mS default OTP.
6	RW	0x0	PWRON_LP_ACT PWRON_LP_ACT: PWRON long press act 0: turn off 1: turn off and then restart
5:4	RW	0x0	PWRON_LP_OFF_TIME PWRON_LP_OFF_TIME: PWRON long press time: 00: 6s, 01: 8s, 10: 10s, 11: 12s
3:2	RW	0x1	PWRON_LP_TM PWRON_LP_TM_SEL<1:0>:PWRON long press interrupt time selection: 00: 0.5S 01:1S 10:1.5S 11:2S
1:0	RW	0x2	PWRON_DB_SEL PWRON_DB_SEL<1:0>:PWRON interrupt debounce time selection: 00: 32uS 01:10mS 10:20mS 11:40mS

**PMIC\_INT\_STS0**

Address: Operational Base + offset (0x00f8)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	W1C	0x0	VB_LO_INT VB_LO_INT: Battery under voltage alarm event interrupt status. reset by power down or RST.
6	W1C	0x0	RTC_PERIOD_INT RTC_PERIOD_INT: RTC period event interrupt. reset by power down or RST.
5	W1C	0x0	RTC_ALARM_INT RTC_ALARM_INT: RTC alarm event interrupt. reset by power down or RST.

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
4	W1C	0x0	HOTDIE_INT HOTDIE_INT: Hot die event interrupt status. reset by power down or RST.
3	W1C	0x0	PWRON_LP_INT PWRON_LP_INT: PWRON PIN long press event interrupt status. reset by power down or RST.
2	W1C	0x0	PWRON_INT PWRON_INT: PWRON event interrupt status. reset by power down or RST.
1	W1C	0x0	PWRON_RISE_INT PWRON_RISE_INT: PWRON rising event interrupt reset by power down or RST.
0	W1C	0x0	PWRON_FALL_INT PWRON_FALL_INT: PWRON falling event interrupt reset by power down or RST.

**PMIC\_INT\_MSK0**

Address: Operational Base + offset (0x00f9)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	VB_LO_IM VB_LO_IM: Battery under voltage alarm event interrupt mask reset by power down or RST.
6	RW	0x0	RTC_PERIOD_IM RTC_PERIOD_IM: RTC period event interrupt mask reset by power down or RST.
5	RW	0x0	RTC_ALARM_IM RTC_ALARM_IM: RTC alarm event interrupt mask reset by power down or RST.
4	RW	0x0	HOTDIE_IM HOTDIE_IM: Hot die event interrupt mask reset by power down or RST.
3	RW	0x0	PWRON_LP_IM PWRON_LP_IM: PWRON PIN long press event interrupt mask reset by power down or RST.

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
2	RW	0x0	PWRON_IM PWRON_IM:PWRON event interrupt mask reset by power down or RST.
1	RW	0x0	PWRON_RISE_INT_IM PWRON_RISE_INT_IM:PWRON rising event interrupt mask reset by power down or RST.
0	RW	0x0	PWRON_FALL_INT_IM PWRON_FALL_INT_IM:PWRON falling event interrupt mask reset by power down or RST.

**PMIC\_INT\_STS1**

Address: Operational Base + offset (0x00fa)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	W1C	0x0	BAT_DIS_ILIM_INT BAT_DIS_ILIM_INT:Battery discharge current over the setting value event interrupt. reset by power down or RST.
6	W1C	0x0	CHRG_IN_CLMP_INT CHRG_IN_CLMP_INT:Charger USB input current limit or USB input voltage limit or chip constant temperature event interrupt (write 1 clear or POWERPATH_EN=0 clear)
5	W1C	0x0	USB_OV_INT USB_OV_INT:USB over voltage event interrupt (write 1 clear or POWERPATH_EN=0 clear)
4	W1C	0x0	CHRG_TS_INT CHRG_TS_INT:Charger TS over or under temperature event interrupt (write 1 clear or POWERPATH_EN=0 clear)
3	W1C	0x0	CHRG_TIME_INT CHRG_TIME_INT:Charger time error event interrupt (write 1 clear or POWERPATH_EN=0 clear)
2	W1C	0x0	CHRG_TERM__INT CHRG_TERM__INT:Charger finished event interrupt (write 1 clear or POWERPATH_EN=0 clear)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
1	W1C	0x0	PLUG_OUT_INT PLUG_OUT_INT: USB plug out event interrupt reset by power down or RST.
0	W1C	0x0	PLUG_IN_INT PLUG_IN_INT: USB plug in event interrupt reset by power down or RST.

**PMIC\_INT\_MSK1**

Address: Operational Base + offset (0x00fb)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	BAT_DIS_ILIM_INT_IM BAT_DIS_ILIM_INT_IM:Battery discharge current over the setting value event interrupt mask. reset by power down or RST.
6	RW	0x0	CHRG_IN_CLMP_INT_IM CHRG_IN_CLMP_INT_IM:Charger USB input current limit or USB input voltage limit or chip constant temperature event interrupt mask.
5	RW	0x0	USB_OV_INT_IMUSB_OV_INT_IM:USB over voltage event interrupt mask
4	RW	0x0	CHRG_TS_INT_IM CHRG_TS_INT_IM:Charger TS over or under temperature event interrupt mask
3	RW	0x0	CHRG_TIME_INT_IM CHRG_TIME_INT_IM:Charger time error event interrupt mask
2	RW	0x0	CHRG_TERM_INT_IM CHRG_TERM_INT_IM:Charger finished event interrupt mask
1	RW	0x0	PLUG_OUT_INT_IM PLUG_OUT_INT_IM: USB plug out event interrupt mask reset by power down or RST.
0	RW	0x0	PLUG_IN_INT_IM PLUG_IN_INT_IM: USB plug in event interrupt mask reset by power down or RST.

**PMIC\_INT\_STS2**

Address: Operational Base + offset (0x00fc)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RC	0x0	CHRG_BAT_HI_INT CHRG_BAT_HI_INT: BAT HI interrupt. reset by power down or RST.
6	W1C	0x0	BAT_OVP_INT BAT_OVP_INT: BAT OVP interrupt. reset by power down or RST.
5	W1C	0x0	CLASSD_OCP_INT CLASSD_OCP_INT: CLASS D OCP interrupt. reset by power down or RST.
4	W1C	0x0	CLASSD_MUTE_DONE CLASSD_MUTE_DONE_INT: CLASSD_MUTE_D ONE interrupt. reset by power down or RST.
3	W1C	0x0	CODEC_PO_INT CODEC_PO_INT: CODEC ANTI-POP DAC SMART POWER ON DONE interrupt. reset by power down or RST.
2	W1C	0x0	CODEC_PD_INT CODEC_PD_INT: CODEC ANTI-POP DAC SMART POWER OFF DONE interrupt. reset by power down or RST.
1	W1C	0x0	TS_GPIO_INT TS_GPIO_INT: TS_GPIO PIN input signal posedge or negedge interrupt. reset by power down or RST.
0	W1C	0x0	GATE_GPIO_INT GATE_GPIO_INT: GATE_GPIO PIN input signal posedge or negedge interrupt. reset by power down or RST.

**PMIC\_INT\_MSK2**

Address: Operational Base + offset (0x00fd)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	CHRG_BAT_HI_INT_IM CHRG_BAT_HI_INT_IM: BAT HI interrupt mask. reset by power down or RST.
6	RW	0x0	BAT_OVP_INT_IM BAT_OVP_INT_IM: BAT OVP interrupt mask. reset by power down or RST.
5	RW	0x0	CLASSD_OCP_INT_IM CLASSD_OCP_INT_IM: CLASS D OCP interrupt mask. reset by power down or RST.

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
4	RW	0x0	CLASSD_MUTE_DONE_IM CLASSD_MUTE_DONE_IM:CLASSD_MUTE_D ONE interrupt mask. reset by power down or RST.
3	RW	0x0	CODEC_PO_INT_IM CODEC_PO_INT_IM:CODEC ANTI-POP DAC SMART POWER ON DONE interrupt mask. reset by power down or RST.
2	RW	0x0	CODEC_PD_INT_IM CODEC_PD_INT_IM:CODEC ANTI-POP DAC SMART POWER OFF DONE interrupt mask. reset by power down or RST.
1	RW	0x0	TS_GPIO_INT_IM TS_GPIO_INT_IM: TS_GPIO PIN input signal posedge or negedge interrupt mask. reset by power down or RST.
0	RW	0x0	GATE_GPIO_INT_IM GATE_GPIO_INT_IM: GATE_GPIO PIN input signal posedge or negedge interrupt mask. reset by power down or RST.

**PMIC\_GPIO\_INT\_CONFIG**

Address: Operational Base + offset (0x00fe)

<b>Bit</b>	<b>Attr</b>	<b>Reset Value</b>	<b>Description</b>
7	RW	0x0	GATE_GPIO_IO GATE_GPIO_IO: GPIO IO definition 0: Input 1: Output, pull high to VCC_RTC
6	RW	0x0	GATE_GPIO_DATA GATE_GPIO_DATA: if GATE pin is GPIO function, it's the data buffer
5	RW	0x1	GATE_GPIO_FUN GATE_GPIO_FUN: GATE pin function 0: GATE function 1:GPIO function
4	RW	0x0	TS_GPIO_IO TS_GPIO_IO: TS GPIO IO definition 0: Input 1: Output, pull high to VCC_RTC
3	RW	0x0	TS_GPIO_DATA TS_GPIO_DATA: if TS pin is GPIO function, it's the data buffer

Bit	Attr	Reset Value	Description
2	RW	0x0	TS_GPIO_FUN TS_GPIO_FUN: TS pin function 0: TS function 1:GPIO function
1	RW	0x1	INT_POL INT_POL: INT pin polarity 0: active low 1: active high reset by power down or RST.
0	RW	0x0	INT_FC_EN INT_FC_EN:interrupt watchdog function enable 0:disable 1:enable reset by power down or RST.

## Chapter 6 Thermal Management

### 6.1 Overview

For reliability and operability concerns, the absolute maximum junction temperature of RK817 has to be below 125°C.

Depending on the thermal mechanical design (Smartphone, Tablet, Personal Navigation Device, etc), the system thermal management software and worst case thermal applications, the junction temperature might be exposed to higher values than those specified above.

Therefore, it is recommended to perform thermal simulations at device level (Smartphone, Tablet, Personal Navigation Device, etc) with the measured power of the worst case UC of the device.

### 6.2 Package Thermal Characteristics

Table 6-1 provides the thermal resistance characteristics for the package used on this device.

Table 6-1 Thermal Resistance Characteristics

PACKAGE (QFN7X7-68)	POWER(W)	$\theta_{JA}$ (°C/W)	$\theta_{JB}$ (°C/W)	$\theta_{JC}$ (°C/W)
RK817	2	21.99	12	6.58

Note: The testing PCB is based on 4 layers, 114mm x 76 mm, 1.6mm thickness, Ambient temperature is 85°C.